ISO 7240-17:2009-08 (E)

Fire detection and fire alarm systems - Part 17: Short-circuit isolators

Contents

Page

Foreword iv

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Requirements 2
4.1 Compliance 2
4.2 Integral status indication 2
4.3 Connection of ancillary devices 2
4.4 Monitoring of detachable short-circuit isolators 3
4.5 Manufacturer's adjustments 3
4.6 On-site adjustments 3
4.7 Marking 3
4.8 Data 3
4.9 Additional requirements for software controlled short-circuit isolators 4

5 Tests 5
5.1 General 5
5.2 Reproducibility 7
5.3 Variation in supply voltage 8
5.4 Dry heat (operational) 8
5.5 Cold (operational) 9
5.6 Damp heat, cyclic (operational) 10
5.7 Damp heat, steady state (endurance) 10
5.8 Sulfur dioxide (SO2) corrosion (endurance) 11
5.9 Shock (operational) 12
5.10 Impact (operational) 13
5.11 Vibration, sinusoidal (operational) 14
5.12 Vibration, sinusoidal (endurance) 15
5.13 Electromagnetic compatibility (EMC), immunity tests (operational) 16

6 Test report 17

Annex A (informative) Examples for the functional test procedure 18

Annex B (informative) Apparatus for impact test 25

Bibliography 27