

DIN EN 54-23:2010-06 (E)

Fire detection and fire alarm systems - Part 23: Fire alarm devices - Visual alarm devices

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | 5 |
| Introduction | | 7 |
| 1 | Scope | 8 |
| 2 | Normative references | 8 |
| 3 | Terms, definitions and abbreviations | 9 |
| 3.1 | Definitions | 9 |
| 3.2 | Abbreviations | 10 |
| 4 | Requirements | 10 |
| 4.1 | General | 10 |
| 4.2 | Operational reliability | 10 |
| 4.2.1 | Duration of operation | 10 |
| 4.2.2 | Provision for external conductors | 10 |
| 4.2.3 | Flammability of materials | 11 |
| 4.2.4 | Enclosure protection | 11 |
| 4.2.5 | Access | 11 |
| 4.2.6 | Manufacturer's adjustments | 11 |
| 4.2.7 | On site adjustments of behaviour | 11 |
| 4.2.8 | Requirements for software controlled devices | 11 |
| 4.3 | Performance parameters under fire conditions | 13 |
| 4.3.1 | Coverage volume | 13 |
| 4.3.2 | Variation of light output | 13 |
| 4.3.3 | Minimum and maximum effective luminous intensity | 13 |
| 4.3.4 | Light colour | 13 |
| 4.3.5 | Light temporal pattern and frequency of flashing | 14 |
| 4.3.6 | Marking and data | 14 |
| 4.3.7 | Synchronization (option with requirements) | 15 |
| 4.4 | Durability | 16 |
| 4.4.1 | Temperature resistance | 16 |
| 4.4.2 | Humidity resistance | 16 |
| 4.4.3 | Shock and vibration resistance | 16 |
| 4.4.4 | Corrosion resistance - Sulphur dioxide (SO ₂) corrosion (endurance) | 16 |
| 4.4.5 | Electrical stability - EMC, immunity (operational) | 17 |
| 5 | Tests and evaluation methods | 17 |
| 5.1 | General | 17 |
| 5.1.1 | Atmospheric conditions for tests | 17 |
| 5.1.2 | Operating conditions for tests | 17 |
| 5.1.3 | Mounting arrangements | 17 |
| 5.1.4 | Tolerances | 18 |
| 5.1.5 | Provision for tests | 18 |
| 5.1.6 | Test schedule | 18 |
| 5.1.7 | Reproducibility | 20 |
| 5.2 | Operational reliability | 20 |
| 5.2.1 | Duration of operation | 20 |
| 5.2.2 | Provision for external conductors | 21 |
| 5.2.3 | Flammability of materials | 21 |

| | | |
|---|--|-----------|
| 5.2.4 | Enclosure protection | 21 |
| 5.2.5 | Access | 22 |
| 5.2.6 | Manufacturer's adjustments | 23 |
| 5.2.7 | On site adjustments of behaviour | 23 |
| 5.2.8 | Requirements for software controlled devices | 23 |
| 5.3 | Performance parameters under fire conditions | 23 |
| 5.3.1 | Coverage volume | 23 |
| 5.3.2 | Variation of luminous intensity | 23 |
| 5.3.3 | Minimum and maximum light intensity | 24 |
| 5.3.4 | Light colour | 24 |
| 5.3.5 | Light pattern and frequency of flashing | 24 |
| 5.3.6 | Marking and data | 24 |
| 5.3.7 | Synchronization (option with requirements) | 24 |
| 5.4 | Durability | 26 |
| 5.4.1 | Temperature resistance | 26 |
| 5.4.2 | Humidity resistance | 29 |
| 5.4.3 | Shock and vibration resistance | 33 |
| 5.4.4 | Corrosion resistance - Sulphur dioxide (SO ₂) corrosion (endurance) | 37 |
| 5.4.5 | Electrical stability - Electromagnetic compatibility (EMC), immunity | 38 |
| 6 | Evaluation of conformity | 39 |
| 6.1 | General | 39 |
| 6.2 | Initial type testing | 40 |
| 6.2.1 | General | 40 |
| 6.2.2 | Test samples | 40 |
| 6.2.3 | Test reports | 40 |
| 6.3 | Factory production control | 41 |
| 6.3.1 | General | 41 |
| 6.3.2 | General requirements | 41 |
| 6.3.3 | Product specific requirements | 42 |
| 6.3.4 | Initial inspection of factory and FPC | 43 |
| 6.3.5 | Surveillance of FPC | 43 |
| 6.4 | Procedure for modifications | 44 |
| 6.5 | One-off products, pre-production products (e.g. prototypes) and products produced in very low quantities | 44 |
| Annex A (normative) Method for measuring the light distribution from a VAD | | 46 |
| A.1 | General | 46 |
| A.2 | Test apparatus | 46 |
| A.3 | Instrumentation | 46 |
| A.4 | Test room | 46 |
| A.5 | Arrangement for measuring the effective luminous intensity | 48 |
| A.6 | Calculation of $l_{eff} (av)$ | 52 |
| A.7 | Calculation of coverage distance | 52 |
| Annex B (normative) Comparative light output level measurement for VADs | | 53 |
| B.1 | General | 53 |
| B.2 | Light test chamber | 53 |
| B.3 | Calibration of the light test chamber | 53 |
| B.4 | Mounting arrangements | 54 |
| B.5 | Measurement of effective average illumination | 54 |
| Annex C (informative) Construction of the light test chamber and associated equipment for comparative measurements | | 55 |
| C.1 | Light test chamber | 55 |
| C.2 | Surface finishes | 55 |
| Annex D (informative) Comparison of flammability test requirements in various standards | | 57 |

| | | |
|--------------|--|-----------|
| D.1 | Introduction | 57 |
| D.2 | Relevant standards | 57 |
| D.3 | Vertical burning tests | 57 |
| D.4 | Horizontal burning tests | 58 |
| D.4.1 | IEC 60695-11-10 and UL 94 | 58 |
| D.4.2 | IEC 60695-11-20 and UL 94 | 59 |
| | | |
| | Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive (89/106/EEC) | 60 |
| | | |
| | ZA.1 Scope and relevant characteristics | 60 |
| | | |
| | ZA.2 Procedures for the attestation of conformity of VADs | 62 |
| | | |
| | ZA.2.1 System of attestation of conformity | 62 |
| | | |
| | ZA.2.2 EC Certificate of conformity | 63 |
| | | |
| | ZA.3 CE marking and labelling | 63 |
| | | |
| | Bibliography | 66 |