

ISO 12239:2010-12 (E)

Smoke alarms using scattered light, transmitted light or ionization

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | General requirements | 4 |
| 4.1 | Compliance | 4 |
| 4.2 | Alarm condition | 4 |
| 4.3 | Mains-on visual indicator | 5 |
| 4.4 | Fault condition visual indicator -- Optional function | 5 |
| 4.5 | Smoke alarm signals | 5 |
| 4.6 | Test facility | 5 |
| 4.7 | Means of calibration | 5 |
| 4.8 | User-replaceable components | 5 |
| 4.9 | Primary power source | 5 |
| 4.10 | Secondary power source | 6 |
| 4.11 | Battery connections | 6 |
| 4.12 | User-replaceable battery | 7 |
| 4.13 | Electrical safety | 7 |
| 4.14 | Connection of external ancillary devices | 7 |
| 4.15 | Terminals for external conductors | 7 |
| 4.16 | Protection against the ingress of foreign bodies | 7 |
| 4.17 | Interconnectable smoke alarms -- Optional function | 8 |
| 4.18 | Alarm-silence facility -- Optional function | 8 |
| 4.19 | Radioactive material in type B smoke alarms | 8 |
| 4.20 | Smoke alarms with voice -- Optional function | 8 |
| 4.21 | Marking | 9 |
| 4.22 | Data | 10 |
| 4.23 | Additional requirements for software controlled smoke alarms | 11 |
| 5 | Tests | 12 |
| 5.1 | General | 12 |
| 5.2 | Directional dependence | 16 |
| 5.3 | Initial sensitivity | 16 |
| 5.4 | Repeatability | 16 |
| 5.5 | Air movement | 17 |
| 5.6 | Dazzling | 17 |
| 5.7 | Dry heat (operational) | 18 |
| 5.8 | Cold (operational) | 19 |
| 5.9 | Damp heat (operational) | 20 |
| 5.10 | Sulfur dioxide (SO ₂) corrosion | 21 |
| 5.11 | Impact (operational) | 22 |
| 5.12 | Vibration, sinusoidal (operational) | 23 |
| 5.13 | Vibration, sinusoidal (endurance) | 24 |
| 5.14 | Extended temperature (operational) -- Optional function | 25 |
| 5.15 | Electromagnetic compatibility (EMC) immunity tests (operational) | 25 |
| 5.16 | Fire sensitivity | 26 |

| | | |
|---|---|----|
| 5.17 | Battery-low condition | 27 |
| 5.18 | 85 dBA Sound output -- Optional function | 28 |
| 5.19 | 70 dBA Sound output -- Optional function | 29 |
| 5.20 | Sounder durability | 30 |
| 5.21 | Interconnectable smoke alarms | 31 |
| 5.22 | Alarm-silence facility | 32 |
| 5.23 | Variation in supply voltage | 32 |
| 5.24 | Polarity reversal | 33 |
| 5.25 | Secondary power source | 34 |
| 5.26 | Electrical safety | 34 |
| 5.27 | Sequence timing for smoke alarms with voice | 35 |
| 6 | Test report | 36 |
| Annex A (normative) Smoke tunnel for response-threshold value measurement | | 37 |
| Annex B (normative) Test aerosol for response threshold value measurements | | 38 |
| Annex C (normative) Smoke-measuring instruments | | 39 |
| Annex D (normative) Apparatus for dazzling test | | 43 |
| Annex E (normative) Apparatus for impact test | | 44 |
| Annex F (normative) Fire test room | | 46 |
| Annex G (normative) Smouldering pyrolysis wood fire (TF2) | | 48 |
| Annex H (normative) Glowing smouldering cotton fire (TF3) | | 51 |
| Annex I (normative) Flaming plastics (polyurethane) fire (TF4) | | 53 |
| Annex J (normative) Flaming liquid (n-heptane) fire (TF5) | | 55 |
| Annex K (informative) Information concerning the construction of the smoke tunnel | | 56 |
| Annex L (informative) Information concerning the construction of the measuring ionization chamber | | 58 |