ISO 7240-6:2011-06 (E)

Fire detection and alarm systems - Part 6: Carbon monoxide fire detectors using electro-chemical cells

Contents

Page

Foreword v

Introduction vii

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Requirements 2
4.1 Compliance 2
4.2 Individual alarm indication 2
4.3 Connection of ancillary devices 2
4.4 Monitoring of detachable detectors 2
4.5 Manufacturer's adjustments 2
4.6 On-site adjustment of response behaviour 3
4.7 Rate-sensitive response behaviour 3
4.8 Marking 3
4.9 Data 4
4.10 Requirements for software controlled detectors 4

5 Test methods 5
5.1 General 5
5.2 Repeatability 8
5.3 Directional dependence 9
5.4 Reproducibility 9
5.5 Exposure to chemical agents at environmental concentrations 10
5.6 Long-term stability 11
5.7 Saturation 11
5.8 Exposure to chemical agents that can be present during a fire 12
5.9 Variation in supply parameters 13
5.10 Air movement 13
5.11 Dry heat (operational) 14
5.12 Cold (operational) 15
5.13 Damp heat cyclic (operational) 16
5.14 Damp heat, steady state (endurance) 17
5.15 Low humidity, steady state (endurance) 17
5.16 Sulfur dioxide (SO2) corrosion (endurance) 18
5.17 Shock (operational) 19
5.18 Impact (operational) 20
5.19 Vibration, sinusoidal (operational) 21
5.20 Vibration, sinusoidal (endurance) 22
5.21 Electromagnetic compatibility (EMC) immunity test (operational) 23
5.22 Fire sensitivity 23

6 Test report 25

Annex A (normative) Gas test chamber for response threshold value and cross-sensitivity measurements 26

Annex B (normative) Apparatus for impact test 27

Annex C (normative) Fire test room 29

Annex D (normative) Smouldering (pyrolysis) wood fire (TF2) 31

Annex E (normative) Glowing smouldering cotton fire (TF3) 34

Annex F (normative) Deep-seated smouldering cotton fire (TF9) 37

Annex G (informative) Information concerning the construction of the gas test chamber 40

Bibliography 42