ISO 7076-2:2012-05 (E)

Fire protection - Foam fire extinguishing systems - Part 2: Low expansion foam equipment

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Requirements 3
4.1 Connections 3
4.2 Parts for removal during routine field maintenance 3
4.3 Corrosion resistance of metal parts 3
4.4 Elastomeric joint rings 3
4.5 Plastics and reinforced resin materials 3
4.6 Strength 4
4.7 Leak resistance 4
4.8 Discharge coefficient (K factor) 4
4.9 Foam quality 4
4.10 Water flow 5
4.11 Range of discharge 5
4.12 Vapour seal 5
4.13 Operation reliability 5
4.14 Stress corrosion 5
4.15 Salt-spray corrosion 5
4.16 Light and water exposure 5
4.17 Heat and fire resistance 6

5 Test methods 6
5.1 General 6
5.2 Ageing test for plastics and reinforced resin materials 6
5.3 Liquid exposure test 6
5.4 Equipment pressurization test 6
5.5 Leak resistance test 6
5.6 Flow coefficient measurement 6
5.7 Measurement of expansion ratio and drainage time 7
5.8 Water flow test 7
5.9 Range tests for branchpipe and monitor 7
5.10 Vapour sealing test 7
5.11 Operation reliability test 7
5.12 Stress corrosion test 8
5.13 Salt-spray corrosion test 8
5.14 Light and water exposure test 9
5.15 Heat and fire resistance 9

6 Marking 9

7 Manufacturer's installation and operation instructions 9

Annex A (normative) Tolerances 10

Bibliography 11