ISO 7240-10:2012-05 (E)

Fire detection and alarm systems - Part 10: Point-type flame detectors

Contents

Page

Foreword iv

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Abbreviated terms 2

5 General requirements 3
5.1 Compliance 3
5.2 Classification 3
5.3 Individual alarm indication 3
5.4 Connection of ancillary devices 3
5.5 Monitoring of detachable detectors 3
5.6 Manufacturer adjustments 3
5.7 On-site sensitivity adjustment 4
5.8 Ingress protection (IP) -- Optional function 4
5.9 Marking 4
5.10 Data 5
5.11 Requirements for software-controlled detectors 5

6 Tests 6
6.1 General 6
6.2 Reproducibility 9
6.3 Repeatability 10
6.4 Directional dependence 10
6.5 Fire sensitivity 11
6.6 Dazzling (operational) 14
6.7 Dry heat (operational) 15
6.8 Cold (operational) 16
6.9 Damp heat, cyclic (operational) 16
6.10 Damp heat, steady state (endurance) 17
6.11 Sulfur dioxide (SO2) corrosion (endurance) 18
6.12 Shock (operational) 19
6.13 Impact (operational) 20
6.14 Vibration, sinusoidal (operational) 21
6.15 Vibration, sinusoidal (endurance) 22
6.16 Variation of supply parameters (operational) 23
6.17 EMC immunity tests (operational) 23
6.18 IP -- Optional function 24

7 Test report 25

Annex A (normative) Apparatus for response point determination 26

Annex B (normative) Liquid (heptane) fire (TF5) 28

Annex C (normative) Liquid (methylated spirit) fire (TF6) 29

Annex D (normative) Apparatus for dazzling test 30

Annex E (normative) Apparatus for impact test 31

Annex F (informative) Example of methane burner 33