

ISO 6182-2:2012-12 (E)

Fire protection - Automatic sprinkler systems - Part 2: Requirements and test methods for wet alarm valves, retard chambers and water motor alarms

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Requirements	3
4.1	Nominal sizes	3
4.2	Connections	3
4.3	Rated working pressure	3
4.4	Bodies and covers	3
4.5	Strength (see 6.9)	4
4.6	Access for maintenance	4
4.7	Components	4
4.8	Leakage (see 6.8)	5
4.9	Non-metallic components (excluding gaskets, seals and other elastomeric parts) (see 6.4 and 6.5)	5
4.10	Sealing assembly elements (see 6.3)	5
4.11	Clearances	5
4.12	Hydraulic friction loss (see 6.7)	7
4.13	Endurance (see 6.6)	8
4.14	Operational performance (see 6.10)	8
4.15	Drains	9
4.16	Alarms (see 6.10.2)	9
4.17	Retard device (see 6.12)	9
4.18	Water motor alarms (see 6.11)	10
5	Production testing and quality control	11
6	Tests	12
6.1	Samples	12
6.2	Spring and diaphragm test	12
6.3	Sealing element tests (see 4.10)	12
6.4	Warm water aging test for non-metallic components (excluding gaskets and seals and other elastomeric parts) (see 4.9)	14
6.5	Air aging test for non-metallic components (excluding gaskets and seals and other elastomeric parts) (see 4.9)	14
6.6	Endurance test (see 4.13)	15
6.7	Hydraulic friction loss test (see 4.12)	15
6.8	Valve leakage and deformation tests (see 4.8)	15
6.9	Body strength test (see 4.5)	16
6.10	Operational test (see 4.14)	16
6.11	Water motor alarm tests (see 4.16)	17
6.12	Retard chamber tests (see 4.17)	18
6.13	Salt mist corrosion test	18
7	Marking	18
8	Manufacturer's installation instructions	19
Annex A (normative)	Tolerances	20