

ISO 6182-3:2012-12 (E)

Fire protection - Automatic sprinkler systems - Part 3: Requirements and test methods for dry pipe valves

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Requirements	3
4.1	Nominal sizes	3
4.2	Connections	3
4.3	Rated working pressure	4
4.4	Bodies and covers	4
4.5	Strength (see 6.9)	4
4.6	Access for maintenance	5
4.7	Components	5
4.8	Leakage (see 6.8)	5
4.9	Non-metallic components (excluding gaskets, seals and other elastomeric parts) (see 6.4 & 6.5)	6
4.10	Sealing assembly elements (see 6.3)	6
4.11	Clearances	6
4.12	Hydraulic friction loss (see 6.7)	8
4.13	Endurance (see 6.6)	9
4.14	Operational performance (see 6.11)	9
4.15	Drains	9
4.16	Alarms (see 6.11)	10
4.17	Valve impairment	10
5	Production testing and quality control	10
6	Tests	10
6.1	Samples	10
6.2	Spring and diaphragm test (see 4.7)	10
6.3	Sealing element tests (see 4.10)	11
6.4	Warm water ageing test for non-metallic components (excluding gaskets and seals) (see 4.9)	11
6.5	Air ageing test for non-metallic components (excluding gaskets and seals)(see 4.9)	12
6.6	Endurance test (see 4.13)	12
6.7	Hydraulic friction loss test (see 4.12)	12
6.8	Valve leakage and deformation test (see 4.8)	12
6.9	Body strength test (see 4.5)	13
6.10	Operational test (see 4.14)	13
6.11	Anti-reseating test (see 4.7.7)	15
6.12	Quick release (see 4.7.8)	15
6.13	Salt mist corrosion test	16
7	Marking	16
8	Manufacturer's installation instructions	17

Annex A (normative) Tolerances	18
Bibliography	19