

ISO/TS 7240-9:2012-12 (E)

Fire detection and alarm systems - Part 9: Test fires for fire detectors

Contents

Page

Foreword	iv
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions and symbols	1
4 Characteristics of test fires -- Description	1
5 Test laboratory	2
5.1 Dimensions	2
5.2 Ambient test conditions	3
5.3 Instruments	3
6 Test method	3
6.1 Arrangement	3
6.2 Ventilation system	4
6.3 Measurement parameters	5
6.4 End-of-test parameters	6
7 Test fires	6
7.1 General	6
7.2 Test fire TF1 -- Open cellulosic (wood) fire	6
7.3 Test fire TF2 -- Rapid smouldering pyrolysis (wood) fire	9
7.4 Test fire TF2a -- Slow smouldering pyrolysis (wood) fire	12
7.5 Test fire TF2b -- Smouldering pyrolysis (wood) fire	14
7.6 Test fire TF3 -- Glowing (fast smouldering) cotton fire	16
7.7 Test fire TF3a -- Glowing (slow smouldering) cotton fire	19
7.8 Test fire TF3b -- Glowing (smouldering) cotton fire	21
7.9 Test fire TF4 -- Open plastics (polyurethane) fire	23
7.10 Test fire TF5 -- Liquid (heptane) fire	26
7.11 Test fire TF5a -- Liquid (heptane) small fire	29
7.12 Test fire TF5b -- Liquid (heptane) medium fire	30
7.13 Test fire TF6 -- Liquid (methylated spirit) fire	32
7.14 Test fire TF7 -- Slow smouldering (pyrolysis) wood fire	33
7.15 Test fire TF8 -- Low temperature black smoke (decalin) liquid fire	34
7.16 Test fire TF9 -- Deep seated smouldering cotton fire	37
Annex A (normative) m value for different light beam lengths	39
Annex B (normative) y value	43
Annex C (normative) Optical measuring instrument	47
Annex D (normative) Measuring ionization chamber (MIC)	48
Annex E (normative) Spark-generating equipment	54