

ISO 7240-23:2013-01 (E)

Fire detection and alarm systems - Part 23: Visual alarm devices

Contents		Page
Foreword		iv
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms, definitions and abbreviations	2
3.1	Terms and definitions	2
3.2	Abbreviations	3
4	Requirements	3
4.1	Compliance	3
4.2	Device class	3
4.3	Minimum and maximum effective light intensity	4
4.4	Light colour	4
4.5	Light pattern and frequency of flashing	4
4.6	Durability	4
4.7	Construction	4
4.8	Manufacturer's adjustments	5
4.9	On-site adjustment of mode or behaviour	5
4.10	Marking and data	5
4.11	Additional requirements for software controlled visual alarm devices	7
4.12	Synchronization -- Optional function	8
5	Tests	8
5.1	General	8
5.2	Reproducibility	10
5.3	Variation of effective luminous intensity	11
5.4	Operational performance	11
5.5	Durability	12
5.6	Dry heat (operational)	12
5.7	Dry heat (endurance)	13
5.8	Cold (operational)	14
5.9	Damp heat, cyclic (operational)	15
5.10	Damp heat, steady-state (endurance)	16
5.11	Damp heat, cyclic (endurance)	17
5.12	Sulfur dioxide (SO₂) corrosion (endurance)	18
5.13	Shock (operational)	19
5.14	Impact (operational)	20
5.15	Vibration, sinusoidal (operational)	21
5.16	Vibration, sinusoidal (endurance)	22
5.17	Electromagnetic compatibility (EMC), immunity (operational)	23
5.18	Enclosure protection	24
5.19	Flash synchronisation testing (optional function)	26
6	Test report	27
Annex A (normative) Method for measuring the light distribution from a visual alarm device		29
Annex B (normative) Comparative light output level measurement for visual alarm devices		36

Annex C (informative)Constructionofthelighttestchamberandassociatedequipmentfor comparative measurements	38
Annex D (informative)Comparisonofflammabilitytestrequirements	40
Bibliography	42