ISO 7240-23:2013-01 (E)

Fire detection and alarm systems - Part 23: Visual alarm devices

Contents

Page

Foreword iv

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms,definitionsandabbreviations 2
3.1 Terms and definitions 2
3.2 Abbreviations 3

4 Requirements 3
4.1 Compliance 3
4.2 Device class 3
4.3 Minimum and maximum effective light intensity 4
4.4 Light colour 4
4.5 Light pattern and frequency of flashing 4
4.6 Durability 4
4.7 Construction 4
4.8 Manufacturer's adjustments 5
4.9 On-site adjustment of mode or behaviour 5
4.10 Marking and data 5
4.11 Additional requirements for software controlled visual alarm devices 7
4.12 Synchronization -- Optional function 8

5 Tests 8
5.1 General 8
5.2 Reproducibility 10
5.3 Variation of effective luminous intensity 11
5.4 Operational performance 11
5.5 Durability 12
5.6 Dry heat (operational) 12
5.7 Dry heat (endurance) 13
5.8 Cold (operational) 14
5.9 Damp heat, cyclic (operational) 15
5.10 Damp heat, steady-state (endurance) 16
5.11 Damp heat, cyclic (endurance) 17
5.12 Sulfur dioxide (SO2) corrosion (endurance) 18
5.13 Shock (operational) 19
5.14 Impact (operational) 20
5.15 Vibration, sinusoidal (operational) 21
5.16 Vibration, sinusoidal (endurance) 22
5.17 Electromagnetic compatibility (EMC), immunity (operational) 23
5.18 Enclosure protection 24
5.19 Flash synchronisation testing (optional function) 26

6 Test report 27

Annex A (normative)Methodformeasuringthelightdistributionfromavisualalarmdevice 29

Annex B (normative) Comparative light output level measurement for visual alarm devices 36

Annex C (informative)Constructionofthelighttestchamberandassociatedequipmentfor comparative measurements 38

Annex D (informative)Comparisonofflammabilitytestrequirements 40

Bibliography 42