DIN EN 14043:2014-04 (E)

High rise aerial appliances for fire and rescue service use - Turntable ladders with combined movement s - Safety and performance requirements and test methods

Contents

Page

Foreword 4

Introduction 7

1 Scope 8

2 Normative references 8

3 Terms and definitions, symbols and abbreviated terms 9

4 List of significant hazards 17

5 Requirements 25
5.1 Safety requirements and/or measures 25
5.1.1 General 25
5.1.2 Requirements in respect of stability 26
5.1.3 Requirements relating to the strength of the turntable ladder 38
5.1.4 Verification of vehicle performance by functional testing 39
5.1.5 Requirements relating to function 41
5.1.6 Requirements relating to noise 68
5.2 Performance requirements 69
5.2.1 Operational requirements 69
5.2.2 Requirements demanded by national regulations 70
5.2.3 Overall maximum dimensions 70
5.2.4 Maximum gross laden mass 71
5.2.5 Radio interference 71

6 Designation 72

7 Information for use 72
7.1 General 72
7.2 Instruction handbook 73
7.2.1 General 73
7.2.2 Operating instruction 73
7.2.3 Transport, handling and storage information 74
7.2.4 Information on commissioning 75
7.2.5 Machine details 75
7.2.6 Maximum loads in the rescue cage and/or on the ladder set 75
7.2.7 Maintenance information for use by trained personnel 75
7.2.8 Special working methods or conditions 76
7.2.9 Periodical examinations and tests 76
7.3 Marking 76

Annex A (informative) **Example of table recording the stability tests** 79

Annex B (normative) **Operating time** 80

Annex C (informative) **List of nominal reaches in several European countries applicable to turntable ladders** 81

Annex D (informative) **Verification and reception tests** 83

Annex ZA (informative) **Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC** 87

Bibliography 88

Figures

Figure 1 — Example of boundary 13
Figure 2 — Jacking width 14
Figure 3 — Designation of ladder set sections 16
Figure 4 — Example of forces acting on turntable ladder 27
Figure 5 — Resulting force of the working load 28
Figure 6 — Surface exposed to the wind 29
Figure 7 — Minimum required residual force related to jacking width 31
Figure 8 — Maximum and minimum jacking width 32
Figure 11 — Static tilt angle δ for turntable ladders 45
Figure 12 — Maximum angle of elevation 47
Figure 13 — Relative positions of hand and guard-rails 49
Figure 14 — Impact simulation on the rescue cage 53
Figure 15 — Rung alignment 60
Figure 16 — Minimum dimensions of ladder sections 63
Figure 17 — Rung spacing dimensions 63
Figure 18 — Winding diameter 67
Figure 19 — Diagram of minimum unaffected zones 72
Figure 20 — Example of a warning label for the number of person permissible in the rescue cage 77

Tables

Table 1 — List of significant hazards 17
Table 2 — Safety factors for load calculations 29
Table 3 — Test cases for verification method 2 34
Table 4 — Functional Safety and Performance Level 53
Table 5 — Functional requirements for ladder set main control console 55
Table 6 — Dimensions 62
Table 7 — Determination of factor c 65
Table 8 — Determination of factor h_1 for the following construction unit 66
Table 9 — Determination of factor h_2 for the following construction unit 67
Table 10 — Nominal reaches 70
Table 11 — Overall maximum dimensions in travel position 70
Table 12 — Maximum gross laden mass 71
Table 13 — Masses taken into consideration in the calculation of gross laden mass 71
Table A.1 — Example of table recording the stability tests 79
Table B.1 — Determination of the operating time 80
Table C.1 — Nominal reaches of turntable ladders in several European countries 81
Table D.1— Verifications and reception tests 83