

DIN EN 54-27:2015-05 (E)

Fire detection and fire alarm systems - Part 27: Duct smoke detectors

Contents		Page
Foreword		5
Introduction		7
1	Scope	8
2	Normative references	8
3	Terms, abbreviated terms and definitions	9
3.1	Terms and definitions	9
3.2	Abbreviated terms	10
4	Requirements	10
4.1	General	10
4.2	Nominal activation conditions/sensitivity	10
4.2.1	Individual alarm indication	10
4.2.2	Additional visual indication (option with requirement)	10
4.2.3	Alarm resetting for stand-alone systems (option with requirement)	11
4.2.4	Connection of ancillary devices (option with requirement)	11
4.2.5	Response to slowly developing fires	11
4.2.6	Dazzling	11
4.3	Operational reliability	11
4.3.1	Repeatability	11
4.3.2	Reproducibility	11
4.3.3	On-site adjustment of response behaviour	11
4.3.4	Manufacturer's adjustments	12
4.3.5	Monitoring of detachable detectors	12
4.3.6	Software controlled detectors (when provided)	12
4.4	Tolerance to supply voltage -- Variation in supply parameters	13
4.5	Performance parameters under fire conditions -- Fire sensitivity	13
4.6	Durability of Nominal activation conditions/sensitivity	13
4.6.1	Temperature resistance	13
4.6.2	Humidity resistance	14
4.6.3	Corrosion resistance -- Sulfur dioxide (SO ₂) corrosion (endurance)	14
4.6.4	Shock and vibration resistance	14
4.6.5	Electrical stability -- EMC, immunity tests (operational)	14
4.6.6	Air leakage	14
5	Testing, assessment and sampling methods	15
5.1	General	15
5.1.1	Atmospheric conditions for tests	15
5.1.2	Operating conditions for tests	15
5.1.3	Mounting arrangements	15
5.1.4	Tolerances	15
5.1.5	Response threshold value	16
5.1.6	Provision for tests	16
5.1.7	Reduced function tests	17
5.1.8	Test schedule	17
5.2	Nominal activation conditions/sensitivity	18
5.2.1	Individual alarm indication	18
5.2.2	Additional visual indication (when provided)	18
5.2.3	Alarm resetting for stand-alone system (when provided)	18

5.2.4	Connection of ancillary devices (when provided)	18
5.2.5	Response to slowly developing fires	18
5.2.6	Dazzling	18
5.3	Operational reliability	19
5.3.1	Repeatability	19
5.3.2	Reproducibility	20
5.3.3	On-site adjustment of response behaviour	20
5.3.4	Manufacturer's adjustments	20
5.3.5	Monitoring of detachable detectors	20
5.3.6	Software controlled devices	20
5.4	Tolerance to supply voltage	20
5.4.1	Variation in supply parameters	20
5.5	Performance parameters under fire conditions	21
5.5.1	Fire sensitivity	21
5.6	Durability of Nominal activation conditions/sensitivity	23
5.6.1	Temperature resistance	23
5.6.2	Humidity resistance	25
5.6.3	Corrosion resistance -- Sulfur dioxide (SO ₂) corrosion (endurance)	27
5.6.4	Shock and vibration resistance	28
5.6.5	Electrical stability	32
5.6.6	Air leakage	33
6	Assessment and verification of constancy of performance (AVCP)	34
6.1	General	34
6.2	Type testing	34
6.2.1	General	34
6.2.2	Test samples, testing and compliance criteria	35
6.2.3	Test reports	35
6.3	Factory production control (FPC)	35
6.3.1	General	35
6.3.2	Requirements	36
6.3.3	Product specific requirements	38
6.3.4	Initial inspection of factory and FPC	39
6.3.5	Continuous surveillance of FPC	39
6.3.6	Procedure for modifications	40
6.3.7	One-off products, pre-production products, (e.g. prototypes) and products produced in very low quantities	40
7	Classification	40
8	Marking, labelling and packaging	41
9	Data	41
Annex A (normative)	Aerosol tunnel arrangement for response measurements	42
Annex B (normative)	Test aerosol for response threshold value measurements	43
Annex C (normative)	Smoke measuring instruments	44
Annex D (normative)	Apparatus for dazzling test	48
Annex E (normative)	Fire test room and working volume arrangements for fire tests	49
Annex F (normative)	Smouldering (pyrolysis) wood fire (TF2D)	51
Annex G (normative)	Flaming plastics (polyurethane) fire (TF4D)	54
Annex H (normative)	Low temperature black smoke (decaline) liquid fire (TF8D)	56
Annex I (informative)	Information concerning the construction of the tunnel for fire tests	59

Annex J (informative) Information concerning the construction of the measuring ionization chamber	61
Annex K (informative) Information about DSD used as a stand-alone system	64
Annex L (informative) Power supply	65
Annex M (informative) Information concerning test procedures and requirements for the response to slowly developing fires	66
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation	70
ZA.1 Scope and relevant characteristics	70
ZA.2 Procedure for assessment and verification of constancy of performance (AVCP) of duct smoke detectors	72
ZA.2.1 System of AVCP	72
ZA.2.2 Declaration of performance (DoP)	73
ZA.3 CE marking and labelling	78
Bibliography	81