DIN EN 54-29:2015-06 (E)

Fire detection and fire alarm systems - Part 29: Multi-sensor fire detectors - Point detectors using a combination of smoke and heat sensors

Contents

Page

Foreword 6

Introduction 8

1 Scope 9

2 Normative references 9

3 Terms and definitions 10

4 Requirements 10
4.1 General 10
4.2 Nominal activation conditions/sensitivity 10
4.2.1 Individual alarm indication 10
4.2.2 Response to slowly developing fires 10
4.2.3 Repeatability of smoke response 11
4.2.4 Directional dependence of smoke response 11
4.2.5 Directional dependence of heat response 11
4.2.6 Lower limit of heat response 11
4.2.7 Reproducibility of smoke response 11
4.2.8 Reproducibility of heat response 11
4.2.9 Air movement 11
4.2.10 Dazzling 11
4.3 Operational reliability 11
4.3.1 Connection of ancillary devices 11
4.3.2 Monitoring of detachable detectors 11
4.3.3 Manufacturer's adjustments 12
4.3.4 On-site adjustment of response behaviour 12
4.3.5 Protection against the ingress of foreign bodies 12
4.3.6 Software controlled detectors 12
4.4 Tolerance to supply parameters 13
4.4.1 Variation in supply parameters 13
4.5 Performance parameters under fire conditions 14
4.5.1 Fire sensitivity 14
4.6 Durability of nominal activation conditions/sensitivity 14
4.6.1 Temperature resistance 14
4.6.2 Humidity resistance 14
4.6.3 Shock and vibration resistance 14
4.6.4 Electrical stability 15
4.6.5 Resistance to chemical agents 15

5 Test and assessment and sampling methods 15
5.1 General 15
5.1.1 Atmospheric conditions for tests 15
5.1.2 Operating conditions for tests 15
5.1.3 Mounting arrangements 15
5.1.4 Tolerances 16
5.1.5 Measurement of smoke response value 16
5.1.6 Measurement of heat response value 16
5.1.7 Provision for tests 17
5.1.8 Test schedule 17

5.2 Nominal activation conditions/sensitivity ... 18
5.2.1 Individual alarm indication ... 18
5.2.2 Response to slowly developing fires ... 19
5.2.3 Repeatability of smoke response ... 19
5.2.4 Directional dependence of smoke response ... 19
5.2.5 Directional dependence of heat response ... 20
5.2.6 Lower limit of heat sensitivity ... 20
5.2.7 Reproducibility of smoke response ... 21
5.2.8 Reproducibility of heat response ... 21
5.2.9 Air movement ... 22
5.2.10 Dazzling ... 22
5.3 Operational reliability ... 23
5.3.1 Connection of ancillary devices ... 23
5.3.2 Monitoring of detachable detectors ... 23
5.3.3 Manufacturer's adjustments ... 23
5.3.4 On-site adjustment of behaviour ... 23
5.3.5 Protection against the ingress of foreign bodies ... 23
5.3.6 Software controlled devices ... 23
5.4 Tolerance to supply parameters ... 24
5.4.1 Variation in supply parameters ... 24
5.5 Performance parameters under fire conditions ... 24
5.5.1 Fire sensitivity ... 24
5.6 Durability of nominal activation conditions/sensitivity ... 26
5.6.1 Temperature resistance ... 26
5.6.2 Humidity resistance ... 28
5.6.3 Shock and vibration resistance ... 30
5.6.4 Electrical stability ... 34
5.6.5 Resistance to chemical agents ... 35

6 Assessment and verification of constancy of performance (AVCP) ... 37
6.1 General ... 37
6.2 Type testing ... 37
6.2.1 General ... 37
6.2.2 Test samples, testing and compliance criteria ... 38
6.2.3 Test reports ... 38
6.3 Factory production control (FPC) ... 38
6.3.1 General ... 38
6.3.2 Requirements ... 39
6.3.3 Product specific requirements ... 41
6.3.4 Initial inspection of factory and FPC ... 42
6.3.5 Continuous surveillance of FPC ... 42
6.3.6 Procedure for modifications ... 42
6.3.7 One-off products, pre-production products, (e.g. prototypes) and products produced in very low quantities ... 43

7 Classification and designation ... 43

8 Marking, Labelling and Packaging ... 44

Annex A (normative) Smoke tunnel for smoke response values ... 45

Annex B (normative) Test aerosol for smoke response value measurements ... 46

Annex C (normative) Smoke measuring instruments ... 47

C.1 Obscuration meter ... 47
C.2 Measuring ionization chamber (MIC) ... 47

Annex D (normative) Heat tunnel for heat response value ... 51

Annex E (normative) Apparatus for dazzling test ... 52

Annex F (informative) Apparatus for impact test 54

Annex G (normative) Fire test room 56

Annex H (normative) Open wood fire (TF1) 58

H.1 Fuel 58
H.2 Arrangement 58
H.3 Method of ignition 58
H.4 Variables 58
H.5 End-of-test condition 58
H.6 Test validity criteria 59

Annex I (normative) Smouldering (pyrolysis) wood fire (TF2) 61

I.1 Fuel 61
I.2 Hotplate 61
I.3 Arrangement 61
I.4 Heating rate 61
I.5 End-of-test condition 61
I.6 Test validity criteria 61

Annex J (normative) Glowing smouldering cotton fire (TF3) 65

J.1 Fuel 65
J.2 Arrangement 65
J.3 Ignition 66
J.4 End-of-test condition 67
J.5 Test validity criteria 67

Annex K (normative) Open plastics (polyurethane) fire (TF4) 69

K.1 Fuel 69
K.2 Conditioning 69
K.3 Arrangement 69
K.4 Ignition 69
K.5 Method of ignition 69
K.6 End-of-test condition 69
K.7 Test validity criteria 69

Annex L (normative) Liquid (heptane) fire (TF5) 71

L.1 Fuel 71
L.2 Arrangement 71
L.3 Ignition 71
L.4 End-of-test condition 71
L.5 Test validity criteria 71

Annex M (normative) Low temperature black smoke (decalene) liquid fire (TF8) 73

M.1 Fuel 73
M.2 Arrangement 73
M.3 Ignition 73
M.4 End-of-test condition 73
M.5 Test validity criteria 73

Annex N (informative) Information concerning the construction of the smoke tunnel 75

Annex O (informative) Construction of the heat tunnel 77

Annex P (informative) Information concerning test procedures and requirements for the response to slowly developing fires 80

Annex Q (informative) Information concerning the construction of the measuring ionization chamber 84

Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation 86

ZA.1 Scope and relevant characteristics 86

ZA.2 Procedure for assessment and verification of constancy of performance (AVCP) of point detectors using a combination of smoke and heat sensors 88

ZA.3 CE marking and labelling 92

Bibliography 96