DIN EN 54-7:2018-10 (E)

Fire detection and fire alarm systems - Part 7: Smoke detectors - Point smoke detectors that operate using scattered light, transmitted light or ionization

Contents

Page

European foreword 5

1 Scope 7

2 Normative references 7

3 Terms and definitions 8

4 Requirements 8
4.1 Compliance 8
4.2 Operational reliability 8
4.2.1 Individual alarm indication 8
4.2.2 Connection of ancillary devices 8
4.2.3 Monitoring of detachable detectors 8
4.2.4 Manufacturer's adjustments 9
4.2.5 On-site adjustment of response behaviour 9
4.2.6 Protection against the ingress of foreign bodies 9
4.2.7 Response to slowly developing fires 9
4.2.8 Software controlled detector (when provided) 10
4.3 Nominal activation conditions/sensitivity 11
4.3.1 Repeatability 11
4.3.2 Directional Dependence 11
4.3.3 Reproducibility 11
4.4 Response delay (response time) 11
4.4.1 Air movement 11
4.4.2 Dazzling 12
4.5 Tolerance to supply voltage -- Variation in supply parameters 12
4.6 Performance parameters under fire conditions -- Fire sensitivity 12
4.7 Durability of Nominal activation conditions/sensitivity 12
4.7.1 Temperature resistance 12
4.7.2 Humidity resistance 12
4.7.3 Corrosion resistance -- Sulfur dioxide (SO2) corrosion (endurance) 12
4.7.4 Vibration resistance 13
4.7.5 Electrical stability -- Electromagnetic Compatibility (EMC), Immunity tests (operational) 13

5 Testing, assessment and sampling methods 13
5.1 General 13
5.1.1 Atmospheric conditions for tests 13
5.1.2 Operating conditions for tests 13
5.1.3 Mounting arrangements 14
5.1.4 Tolerances 14
5.1.5 Measurement of response value 14
5.1.6 Provision for tests 15
5.1.7 Test schedule 15
5.2 Operational reliability 17
5.2.1 Individual alarm indication 17
5.2.2 Connection of ancillary devices 17
5.2.3 Monitoring of detachable detectors 17
5.2.4 Manufacturer's adjustments 17
5.2.5 On-site adjustment of response behaviour 17
5.2.6 Protection against the ingress of foreign bodies 17

5.2.7 Response to slowly developing fires ... 18
5.2.8 Software controlled detector (when provided) ... 18
5.3 Nominal activation conditions/sensitivity ... 18
5.3.1 Repeatability ... 18
5.3.2 Directional dependence ... 18
5.3.3 Reproducibility ... 19
5.4 Response delay (response time) ... 19
5.4.1 Air movement ... 19
5.4.2 Dazzling ... 20
5.5 Tolerance to supply voltage -- Variation in supply parameters ... 21
5.5.1 Object ... 21
5.5.2 Test procedure ... 21
5.5.3 Requirements ... 21
5.6 Performance parameters under fire conditions ... 21
5.6.1 Fire sensitivity ... 21
5.7 Durability of Nominal activation conditions/sensitivity ... 23
5.7.1 Temperature resistance ... 23
5.7.2 Humidity resistance ... 24
5.7.3 Corrosion resistance -- Sulfur dioxide (SO2) corrosion (endurance) ... 26
5.7.4 Vibration resistance ... 27
5.7.5 Electrical stability ... 31

6 Assessment and verification of constancy of performance (AVCP) ... 32
6.1 General ... 32
6.2 Type testing ... 32
6.2.1 General ... 32
6.2.2 Test samples, testing and compliance criteria ... 33
6.2.3 Test reports ... 33
6.3 Factory production control (FPC) ... 33
6.3.1 General ... 33
6.3.2 Requirements ... 34
6.3.3 Product specific requirements ... 36
6.3.4 Initial inspection of factory and FPC ... 37
6.3.5 Continuous surveillance of FPC ... 37
6.3.6 Procedure for modifications ... 37
6.3.7 One-off products, pre-production products, (e.g. prototypes) and products produced in very low quantities ... 38

7 Classification ... 38

8 Marking, labelling and packaging ... 38

Annex A (normative) Smoke tunnel for response value measurements ... 40

Annex B (normative) Test aerosol for response value measurements ... 41

Annex C (normative) Smoke measuring instruments ... 42

C.1 Obscuration meter ... 42
C.2 Measuring ionization chamber (MIC) ... 42
C.2.1 General ... 42
C.2.2 Operating method and basic construction ... 43
C.2.3 Technical data ... 44

Annex D (normative) Apparatus for dazzling test ... 46

Annex E (informative) Apparatus for impact test ... 48

Annex F (normative) Fire test room ... 50

Annex G (normative) Smouldering (pyrolysis) wood fire (TF2) ... 52

G.1 Fuel 52
G.2 Hotplate 52
G.3 Arrangement 52
G.4 Heating rate 53
G.5 End of test condition 53
G.6 Test validity criteria 53

Annex H (normative) Glowing smouldering cotton fire (TF3) 55

H.1 Fuel 55
H.2 Arrangement 55
H.3 Ignition 55
H.4 End of test condition 56
H.5 Test validity criteria 56

Annex I (normative) Flaming plastics (polyurethane) fire (TF4) 57

I.1 Fuel 57
I.2 Arrangement 57
I.3 Ignition 57
I.4 End of test condition 57
I.5 Test validity criteria 57

Annex J (normative) Flaming liquid (n-heptane) fire (TF5) 59

J.1 Fuel 59
J.2 Arrangement 59
J.3 Ignition 59
J.4 End of test condition 59
J.5 Test validity criteria 59

Annex K (informative) Information concerning the construction of the smoke tunnel 61

Annex L (informative) Information concerning the requirements for the response to slowly developing fires 64

Annex M (informative) Information concerning the construction of the measuring ionization chamber 68

Annex N (normative) Test set-up for testing the protection against the effect of moving objects 71

Annex O (normative) Apparatus open detector static object test 73

Annex P (informative) Data supplied with point smoke detectors 74

Annex ZA (informative) Relationship of this European Standard with Regulation (EU) No.305/2011 75

ZA.1 Scope and relevant characteristics 75

ZA.2 System of Assessment and Verification of Constancy of Performance (AVCP) 77

ZA.3 Assignment of AVCP tasks 77

Bibliography 79