

ISO 7076-3:2016-07 (E)

Fire protection - Foam fire extinguishing systems - Part 3: Medium expansion foam equipment

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Requirements | 2 |
| 4.1 | Connections | 2 |
| 4.1.1 | Permanent connections and joints | 2 |
| 4.1.2 | Bolting of pressure-retaining parts | 2 |
| 4.2 | Parts for removal during routine field maintenance | 2 |
| 4.2.1 | Removal | 2 |
| 4.2.2 | Re-assembly | 2 |
| 4.3 | Corrosion resistance of metal parts | 2 |
| 4.4 | Elastomeric joint rings | 3 |
| 4.4.1 | General | 3 |
| 4.4.2 | Resistance to aging | 3 |
| 4.4.3 | Resistance to exposure to liquids | 3 |
| 4.5 | Plastics and reinforced resin materials | 3 |
| 4.5.1 | General | 3 |
| 4.5.2 | Resistance to ageing | 3 |
| 4.5.3 | Resistance to exposure to liquids | 4 |
| 4.6 | Strength | 4 |
| 4.7 | Leak resistance | 4 |
| 4.8 | Discharge coefficient (K factor) | 4 |
| 4.9 | Foam quality | 4 |
| 4.10 | Water flow | 5 |
| 4.11 | Operation reliability | 5 |
| 4.12 | Stress corrosion | 5 |
| 4.13 | Salt-spray corrosion | 5 |
| 4.14 | Light and water exposure | 5 |
| 4.15 | Heat and fire resistance | 5 |
| 5 | Test methods | 5 |
| 5.1 | General | 5 |
| 5.2 | Ageing test for plastics and reinforced resin materials | 6 |
| 5.3 | Liquid exposure test | 6 |
| 5.4 | Equipment pressurization test | 6 |
| 5.5 | Leak resistance test | 6 |
| 5.6 | Flow coefficient measurement | 6 |
| 5.7 | Measurement of expansion ratio and drainage time | 6 |
| 5.8 | Water flow test | 7 |
| 5.9 | Operation reliability test | 7 |
| 5.10 | Stress corrosion test | 7 |
| 5.11 | Salt-spray corrosion test | 8 |
| 5.12 | Light and water exposure test | 8 |
| 5.13 | Heat and fire resistance test | 8 |
| 6 | Marking | 8 |

| | | |
|----------|---|-----------|
| 7 | Manufacturer's installation and operation instructions | 9 |
| | Annex A (normative) Tolerances | 10 |
| | Bibliography | 11 |