DIN EN 54-5:2017-05 (E)

Fire detection and fire alarm systems - Part 5: Heat detectors - Point heat detectors

Contents

Page

European foreword 5

1 Scope 7

2 Normative references 7

3 Terms, definitions and abbreviations 8
3.1 Terms and Definitions 8
3.2 Abbreviations 8

4 Product characteristics 8
4.1 General 8
4.1.1 Heat Response Categories 8

Table 1 -- Detector categorization temperatures 9
4.2 Operational reliability 9
4.2.1 Position of heat sensitive elements 9
4.2.2 Individual alarm indication 9
4.2.3 Connection of ancillary devices 10
4.2.4 Monitoring of detachable detectors 10
4.2.5 Manufacturer's adjustments 10
4.2.6 On-site adjustment of response behaviour 10
4.2.7 Software controlled detector (when provided) 10
4.3 Nominal activation conditions/sensitivity 12
4.3.1 Directional dependence 12
4.3.2 Static response temperature 12
4.3.3 Response times from typical application temperature 12
4.3.4 Response times from 25 °C 12
4.3.5 Response times from high ambient temperature 12
4.3.6 Reproducibility 12
4.4 Response delay (response time) 13
4.4.1 Additional tests for suffix S detectors 13
4.4.2 Additional tests for suffix R detectors 13
4.5 Tolerance to supply voltage - Variation in supply parameters 13
4.6 Durability of Nominal activation conditions/sensitivity 13
4.6.1 Temperature resistance 13
4.6.2 Humidity resistance 13
4.6.3 Corrosion resistance: Sulphur dioxide (SO_2) corrosion (endurance) 14
4.6.4 Vibration resistance 14
4.6.5 Electrical stability: Electromagnetic Compatibility (EMC), Immunity tests (operational) 14

5 Testing, assessment and sampling methods 14
5.1 General 14
5.1.1 Atmospheric conditions for tests 14
5.1.2 Operating conditions for tests 15
5.1.3 Mounting arrangements 15
5.1.4 Tolerances 15
5.1.5 Measurement of response time 15
5.1.6 Provision for tests 16
5.1.7 Test schedule 16

Table 2 -- Test schedule for resettable point heat detectors 17

Table 3 -- Test schedule for non-resettable point heat detectors 18
5.2 Operational reliability 20
5.2.1 Position of heat sensitive elements 20
5.2.2 Individual alarm indication 20
5.2.3 Connection of ancillary devices 20
5.2.4 Monitoring of detachable detectors 20
5.2.5 Manufacturer's adjustments 20
5.2.6 On-site adjustment of response behaviour 20
5.2.7 Software controlled detectors (when provided) 20
5.3 Nominal activation conditions/sensitivity 21
5.3.1 Directional dependence 21
5.3.2 Static response temperature 21
5.3.3 Response times from typical application temperature 22

Table 4 -- Response time limits 22
5.3.4 Response times from 25 °C 22
5.3.5 Response times from high ambient temperature 23

Table 5 -- Response time limits from maximum application temperature 24
5.3.6 Reproducibility 24
5.4 Response delay (response time) 24
5.4.1 Additional tests for suffix S detectors 24

Table 6 -- Conditioning and airflow temperatures 25

Table 7 -- Lower limit of response for category suffix S point heat detectors 25
5.4.2 Additional test for suffix R detectors 26

Table 8 -- Initial conditioning temperature for suffix R point heat detectors 26
5.5 Tolerance to supply voltage 26
5.5.1 Variation in supply parameters 26
5.6 Durability of Nominal activation conditions/sensitivity 27
5.6.1 Temperature resistance 27

Table 9 -- Dry heat (endurance) conditioning temperatures 29
5.6.2 Humidity resistance 29
5.6.3 Corrosion resistance 31
5.6.4 Vibration resistance 33
5.6.5 Electrical stability 37

6 Assessment and verification of constancy of performance (AVCP) 38
6.1 General 38
6.2 Type testing 39
6.2.1 General 39
6.2.2 Test samples, testing and compliance criteria 39

Table 10 -- Number of samples to be tested and compliance criteria 40
6.2.3 Test reports 40
6.3 Factory production control FPC) 40
6.3.1 General 40
6.3.2 Requirements 41
6.3.3 Product specific requirements 43
6.3.4 Initial inspection of factory and FPC 44
6.3.5 Continuous surveillance of FPC 44
6.3.6 Procedure for modifications 44
6.3.7 One-off products, pre-production products, (e.g. prototypes) and products produced in very low quantities 45

7 Classification 45

8 Marking, labelling and packaging 45

Annex A (normative) Heat tunnel for response time and response temperature measurements 47

Annex B (informative) Information concerning the construction of the heat tunnel 48

Figure B.1 -- Example of working section of heat tunnel 49

Figure B.2 -- Example of mounting arrangement for simultaneously testing two point heat detectors (section A - A, see Figure B.1) 50

Annex C (informative) Derivation of upper and lower limits of response times 51

Table C.1 -- Thermal constants used to derive upper limits in Table 4 52

Annex D (informative) Apparatus for impact test 54

Figure D.1 -- Impact apparatus 55

Annex E (informative) Data supplied with point heat detectors 56

Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation 57

ZA.1 Scope and relevant characteristics 57

Table ZA.1 -- Relevant clauses for point heat detectors and intended use in fire detection and fire alarm systems installed in and around buildings 57

ZA.2 Procedure for assessment and verification of constancy of performance (AVCP) of point heat detector 59

ZA.2.1 System of AVCP 59

Table ZA.2 -- System of AVCP 59

Table ZA.3 -- Assignment of evaluation of conformity tasks for point heat detectors under system 1 60

ZA.2.2 Declaration of performance (DoP) 60

ZA.2.2.1 General 60

ZA.2.2.2 Content 61

ZA.2.2.3 Example of DoP 62

ZA.3 CE marking and labelling 68

Bibliography 72