

DIN EN 54-5:2017-05 (E)

Fire detection and fire alarm systems - Part 5: Heat detectors - Point heat detectors

Contents		Page
European foreword		5
1	Scope	7
2	Normative references	7
3	Terms, definitions and abbreviations	8
3.1	Terms and Definitions	8
3.2	Abbreviations	8
4	Product characteristics	8
4.1	General	8
4.1.1	Heat Response Categories	8
Table 1 -- Detector categorization temperatures		9
4.2	Operational reliability	9
4.2.1	Position of heat sensitive elements	9
4.2.2	Individual alarm indication	9
4.2.3	Connection of ancillary devices	10
4.2.4	Monitoring of detachable detectors	10
4.2.5	Manufacturer's adjustments	10
4.2.6	On-site adjustment of response behaviour	10
4.2.7	Software controlled detector (when provided)	10
4.3	Nominal activation conditions/sensitivity	12
4.3.1	Directional dependence	12
4.3.2	Static response temperature	12
4.3.3	Response times from typical application temperature	12
4.3.4	Response times from 25 °C	12
4.3.5	Response times from high ambient temperature	12
4.3.6	Reproducibility	12
4.4	Response delay (response time)	13
4.4.1	Additional tests for suffix S detectors	13
4.4.2	Additional tests for suffix R detectors	13
4.5	Tolerance to supply voltage - Variation in supply parameters	13
4.6	Durability of Nominal activation conditions/sensitivity	13
4.6.1	Temperature resistance	13
4.6.2	Humidity resistance	13
4.6.3	Corrosion resistance: Sulphur dioxide (SO₂) corrosion (endurance)	14
4.6.4	Vibration resistance	14
4.6.5	Electrical stability: Electromagnetic Compatibility (EMC), Immunity tests (operational) ...	14
5	Testing, assessment and sampling methods	14
5.1	General	14
5.1.1	Atmospheric conditions for tests	14
5.1.2	Operating conditions for tests	15
5.1.3	Mounting arrangements	15
5.1.4	Tolerances	15
5.1.5	Measurement of response time	15
5.1.6	Provision for tests	16
5.1.7	Test schedule	16
Table 2 -- Test schedule for resettable point heat detectors		17

Table 3 -- Test schedule for non-resettable point heat detectors	18
5.2 Operational reliability	20
5.2.1 Position of heat sensitive elements	20
5.2.2 Individual alarm indication	20
5.2.3 Connection of ancillary devices	20
5.2.4 Monitoring of detachable detectors	20
5.2.5 Manufacturer's adjustments	20
5.2.6 On-site adjustment of response behaviour	20
5.2.7 Software controlled detectors (when provided)	20
5.3 Nominal activation conditions/sensitivity	21
5.3.1 Directional dependence	21
5.3.2 Static response temperature	21
5.3.3 Response times from typical application temperature	22
Table 4 -- Response time limits	22
5.3.4 Response times from 25 °C	22
5.3.5 Response times from high ambient temperature	23
Table 5 -- Response time limits from maximum application temperature	24
5.3.6 Reproducibility	24
5.4 Response delay (response time)	24
5.4.1 Additional tests for suffix S detectors	24
Table 6 -- Conditioning and airflow temperatures	25
Table 7 -- Lower limit of response for category suffix S point heat detectors	25
5.4.2 Additional test for suffix R detectors	26
Table 8 -- Initial conditioning temperature for suffix R point heat detectors	26
5.5 Tolerance to supply voltage	26
5.5.1 Variation in supply parameters	26
5.6 Durability of Nominal activation conditions/sensitivity	27
5.6.1 Temperature resistance	27
Table 9 -- Dry heat (endurance) conditioning temperatures	29
5.6.2 Humidity resistance	29
5.6.3 Corrosion resistance	31
5.6.4 Vibration resistance	33
5.6.5 Electrical stability	37
6 Assessment and verification of constancy of performance (AVCP)	38
6.1 General	38
6.2 Type testing	39
6.2.1 General	39
6.2.2 Test samples, testing and compliance criteria	39
Table 10 -- Number of samples to be tested and compliance criteria	40
6.2.3 Test reports	40
6.3 Factory production control (FPC)	40
6.3.1 General	40
6.3.2 Requirements	41
6.3.3 Product specific requirements	43
6.3.4 Initial inspection of factory and FPC	44
6.3.5 Continuous surveillance of FPC	44
6.3.6 Procedure for modifications	44
6.3.7 One-off products, pre-production products, (e.g. prototypes) and products produced in very low quantities	45
7 Classification	45
8 Marking, labelling and packaging	45

Annex A (normative) Heat tunnel for response time and response temperature measurements	47
Annex B (informative) Information concerning the construction of the heat tunnel	48
Figure B.1 -- Example of working section of heat tunnel	49
Figure B.2 -- Example of mounting arrangement for simultaneously testing two point heat detectors (section A - A, see Figure B.1)	50
Annex C (informative) Derivation of upper and lower limits of response times	51
Table C.1 -- Thermal constants used to derive upper limits in Table 4	52
Annex D (informative) Apparatus for impact test	54
Figure D.1 -- Impact apparatus	55
Annex E (informative) Data supplied with point heat detectors	56
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation	57
ZA.1 Scope and relevant characteristics	57
Table ZA.1 -- Relevant clauses for point heat detectors and intended use in fire detection and fire alarm systems installed in and around buildings	57
ZA.2 Procedure for assessment and verification of constancy of performance (AVCP) of point heat detector	59
ZA.2.1 System of AVCP	59
Table ZA.2 -- System of AVCP	59
Table ZA.3 -- Assignment of evaluation of conformity tasks for point heat detectors under system 1	60
ZA.2.2 Declaration of performance (DoP)	60
ZA.2.2.1 General	60
ZA.2.2.2 Content	61
ZA.2.2.3 Example of DoP	62
ZA.3 CE marking and labelling	68
Bibliography	72