ISO 7240-2:2017-11 (E)

Fire detection and alarm systems - Part 2: Fire detection control and indicating equipment

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Normative references 1

3 Terms,definitionsandabbreviatedterms 1

4 Requirements 2
4.1 General 2
4.2 Compliance 3
4.3 Quiescent condition 3
4.4 Fire alarm condition 3
4.4.1 Reception and processing of fire signals 3
4.4.2 Indication of fire alarm condition 4
4.4.3 Indication of fire detection zones in alarm 4
4.4.4 Audible indication 4
4.4.5 Other indications during the fire alarm condition 5
4.4.6 Reset from fire alarm condition 5
4.4.7 Output of fire alarm condition 5
4.4.8 Output to fire alarm signalling function -- Optional function 5
4.4.9 Control of fire alarm routing function -- Optional function 6
4.4.10 Output to fire protection control function -- Optional function 6
4.4.11 Delays to outputs -- Optional function 7
4.4.12 Dependency on more than one alarm signal -- Optional function 8
4.4.13 Alarm counter -- Optional function 9
4.4.14 Output of standard emergency evacuation signal -- Optional function 9
4.5 Fault warning condition 9
4.5.1 Reception and processing of fault signals 9
4.5.2 Indication of faults 9
4.5.3 Fault monitoring of fire protection control function -- Optional function 11
4.5.4 Fault signals from points -- Optional function 11
4.5.5 Total loss of the power supply -- Optional function 11
4.5.6 System fault 11
4.5.7 Audible indication 11
4.5.8 Reset of fault indications 12
4.5.9 Fault output 12
4.5.10 Output to fault warning routing function -- Optional function 12
4.6 Disabled condition -- Optional function 12
4.6.1 General 12
4.6.2 Disablements 13
4.6.3 Disablement and enablement of addressable points -- Optional function 13
4.6.4 Indication of the disabled condition 13
4.7 Test condition -- Optional function 14
4.7.1 General requirements 14
4.7.2 Indication of test condition 14
4.7.3 Indication of fire detection zones in test state 14
4.8 Supervisory signal condition -- Optional function 14
4.8.1 Reception and processing of supervisory signals 14

4.8.2 Indication of the supervisory signal condition 15
4.8.3 Indication of the supervisory signals from fire detection zones 15
4.8.4 Audible indication 15
4.8.5 Reset of supervisory signal 16
4.8.6 Supervisory signal condition output 16
4.9 Standardized input/output interface -- Optional function 16
4.10 Accessibility of indications and controls 17
4.11 Visual indications 17
4.11.1 General 17
4.11.2 Indications by means of light-emitting indicators 17
4.11.3 Indications on alphanumeric displays 18
4.12 Audible indications 19
4.13 Additional indications 19
4.14 Testing of indicators 19
4.15 Power supply 19
4.16 Mechanical 19
4.17 Integrity of transmission paths 20
4.18 Software 20
4.18.1 General 20
4.18.2 Program monitoring 20
4.18.3 Storage of programs and data 21
4.18.4 Monitoring of memory contents 21

5 Tests 21
5.1 General 21
5.1.1 Standard atmospheric conditions for testing 21
5.1.2 Specimen configuration 22
5.1.3 Mounting and orientation 22
5.1.4 Electrical connection 22
5.1.5 Provision for tests 22
5.2 Functional test 22
5.2.1 Object of test 22
5.2.2 Test schedule 22
5.2.3 Fire alarm condition 23
5.2.4 Fault warning condition 23
5.2.5 Disabled condition 23
5.2.6 Requirements 23
5.3 Environmental tests 23
5.3.1 General 23
5.3.2 Tests for one specimen 24
5.3.3 Tests for two specimens 24
5.3.4 Tests for three specimens 24
5.3.5 Requirements 24
5.4 Cold (operational) 24
5.4.1 Object of test 24
5.4.2 Test procedure 25
5.4.3 Requirements 25
5.5 Damp heat, steady-state (operational) 25
5.5.1 Object of test 25
5.5.2 Test procedure 26
5.5.3 Requirements 26
5.6 Impact (operational) -- Optional test 26
5.6.1 Object of test 26
5.6.2 Test procedure 27
5.6.3 Requirements 27
5.7 Vibration, sinusoidal (operational) -- Optional test 28
5.7.1 Object of test 28
5.7.2 Test procedure 28
5.7.3 Requirements 29
5.8 Electromagnetic compatibility (EMC) -- Immunity tests (operational) 29
5.8.1 Test procedure 29

5.8.2 Requirements 30
5.9 Supply voltage variation (operational) 30
5.9.1 Object of test 30
5.9.2 Test procedure 30
5.9.3 Requirements 30
5.10 Damp heat, steady-state (endurance) 31
5.10.1 Object of test 31
5.10.2 Test procedure 31
5.10.3 Requirements 31
5.11 Vibration, sinusoidal (endurance) 32
5.11.1 Object of test 32
5.11.2 Test procedure 32
5.11.3 Requirements 32
5.12 Dry heat (operational) -- Optional 33
5.12.1 Object of test 33
5.12.2 Test procedure 33
5.12.3 Requirements 33

6 Test report 33

7 Marking 34

8 Data 34
8.1 General 34
8.2 Software documentation 34
8.3 Hardware documentation 35
8.4 Installation and user documentation 35

Annex A (informative) Optional functions with requirements and alternatives 37

Annex B (informative)Processingofsignalsfromfiredetectors 38

Annex C (informative)Explanationoffiredetectionzonesandzonalindicationoffirealarms 39

Annex D (informative) Delays to outputs 40

Annex E (informative) Fault recognition and indication 42

Annex F (informative) Systems related to the supervisory signal condition 43

Annex G (informative)Standardizedinput/outputinterfacefortheconnectionofancillary equipment(e.g.firebrigadepanel) 44

Annex H (informative) Explanation of access levels 45

Annex I (informative) Integrity of transmission paths 47

Annex J (informative)Designrequirementsforsoftware-controlledfiredetectioncontrol and indicating equipment 48

Bibliography 49