

ISO 7240-5:2018 (E)

Fire detection and fire alarm systems — Part 5: Point type heat detectors

Contents

| | |
|-------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | General requirements |
| 4.1 | Compliance |
| 4.2 | Classification |
| 4.3 | Position of heat sensitive elements |
| 4.4 | Individual alarm indication |
| 4.5 | Connection of ancillary devices |
| 4.6 | Monitoring of detachable detectors |
| 4.7 | Manufacturer's adjustments |
| 4.8 | On-site adjustment of response behaviour |
| 4.9 | Requirements for software controlled detectors |
| 4.9.1 | General |
| 4.9.2 | Software design |
| 4.9.3 | The storage of programs and data |
| 5 | Tests |
| 5.1 | General |
| 5.1.1 | Atmospheric conditions for tests |
| 5.1.2 | Operating conditions for tests |
| 5.1.3 | Mounting arrangements |
| 5.1.4 | Tolerances |
| 5.1.5 | Measurement of response time |
| 5.1.6 | Provision for tests |
| 5.1.7 | Test schedule |
| 5.2 | Directional dependence |
| 5.2.1 | Object |
| 5.2.2 | Test procedure |
| 5.2.3 | Requirements |
| 5.3 | Static response temperature |
| 5.3.1 | Object |
| 5.3.2 | Test procedure |
| 5.3.3 | Requirements |
| 5.4 | Response times from typical application temperature |
| 5.4.1 | Object |
| 5.4.2 | Test procedure |
| 5.4.3 | Requirements |
| 5.5 | Response times from 25 °C |
| 5.5.1 | Object |
| 5.5.2 | Test procedure |
| 5.5.3 | Requirements |
| 5.6 | Response times from high ambient temperature (Dry heat operational) |
| 5.6.1 | Object |
| 5.6.2 | Test procedure |
| 5.6.3 | Requirements |
| 5.7 | Variation in supply parameters |
| 5.7.1 | Object |

| | |
|----------|---|
| 5.7.2 | Test procedure |
| 5.7.3 | Requirements |
| 5.8 | Reproducibility |
| 5.8.1 | Object |
| 5.8.2 | Test procedure |
| 5.8.3 | Requirements |
| 5.9 | Cold (operational) |
| 5.9.1 | Object |
| 5.9.2 | Test procedure |
| 5.9.2.1 | Reference |
| 5.9.2.2 | State of the specimen(s) during conditioning |
| 5.9.2.3 | Conditioning |
| 5.9.2.4 | Measurements during conditioning |
| 5.9.2.5 | Final measurements |
| 5.9.3 | Requirements |
| 5.10 | Dry heat (endurance) |
| 5.10.1 | Object |
| 5.10.2 | Test procedure |
| 5.10.2.1 | Reference |
| 5.10.2.2 | State of the specimen during conditioning |
| 5.10.2.3 | Conditioning |
| 5.10.2.4 | Final measurements |
| 5.10.3 | Requirements |
| 5.11 | Damp heat, cyclic (operational) |
| 5.11.1 | Object |
| 5.11.2 | Test procedure |
| 5.11.2.1 | Reference |
| 5.11.2.2 | State of the specimen during conditioning |
| 5.11.2.3 | Conditioning |
| 5.11.2.4 | Measurements during conditioning |
| 5.11.2.5 | Final measurements |
| 5.11.3 | Requirements |
| 5.12 | Damp heat, steady state (endurance) |
| 5.12.1 | Object |
| 5.12.2 | Test procedure |
| 5.12.2.1 | Reference |
| 5.12.2.2 | State of the specimen(s) during conditioning |
| 5.12.2.3 | Conditioning |
| 5.12.2.4 | Final measurements |
| 5.12.3 | Requirements |
| 5.13 | Sulphur dioxide SO ₂ corrosion (endurance) |
| 5.13.1 | Object |
| 5.13.2 | Test procedure |
| 5.13.2.1 | Reference |
| 5.13.2.2 | State of the specimen during conditioning |
| 5.13.2.3 | Conditioning |
| 5.13.2.4 | Final measurements |
| 5.13.3 | Requirements |
| 5.14 | Shock (operational) |
| 5.14.1 | Object |
| 5.14.2 | Test procedure |
| 5.14.2.1 | Reference |
| 5.14.2.2 | State of the specimen during conditioning |
| 5.14.2.3 | Conditioning |
| 5.14.2.4 | Measurements during conditioning |
| 5.14.2.5 | Final measurements |
| 5.14.3 | Requirements |
| 5.15 | Impact (operational) |
| 5.15.1 | Object |
| 5.15.2 | Test procedure |
| 5.15.2.1 | Apparatus |
| 5.15.2.2 | State of the specimen during conditioning |
| 5.15.2.3 | Conditioning |
| 5.15.2.4 | Measurements during conditioning |

| | |
|----------|---|
| 5.15.2.5 | Final measurements |
| 5.15.3 | Requirements |
| 5.16 | Vibration, sinusoidal, (operational) |
| 5.16.1 | Object |
| 5.16.2 | Test procedure |
| 5.16.2.1 | Reference |
| 5.16.2.2 | State of the specimen during conditioning |
| 5.16.2.3 | Conditioning |
| 5.16.2.4 | Measurements during conditioning |
| 5.16.2.5 | Final measurements |
| 5.16.3 | Requirements |
| 5.17 | Vibration, sinusoidal (endurance) |
| 5.17.1 | Object |
| 5.17.2 | Test procedure |
| 5.17.2.1 | Reference |
| 5.17.2.2 | State of the specimen during conditioning |
| 5.17.2.3 | Conditioning |
| 5.17.2.4 | Final measurements |
| 5.17.3 | Requirements |
| 5.18 | Electromagnetic Compatibility (EMC), Immunity tests (operational) |
| 5.18.1 | Test procedure |
| 5.18.1.1 | Reference |
| 5.18.1.2 | Final measurements |
| 5.18.2 | Requirements |
| 5.19 | Test for suffix S detectors |
| 5.19.1 | Object |
| 5.19.2 | Test procedure |
| 5.19.2.1 | Plunge test |
| 5.19.2.2 | Review of response time data |
| 5.19.3 | Requirements |
| 5.20 | Additional test for suffix R detector |
| 5.20.1 | Object |
| 5.20.2 | Test procedure |
| 5.20.3 | Requirements |
| 6 | Test report |
| 7 | Marking |
| 8 | Data |
| 8.1 | Hardware documentation |
| 8.2 | Software documentation |
| Annex A | (normative) Heat tunnel for response time and response temperature measurements |
| Annex B | (informative) Information concerning the construction of the heat tunnel |
| Annex C | (informative) Derivation of upper and lower limits of response times |
| C.1 | Upper limits |
| C.2 | Lower limits |
| C.3 | Change after environmental tests |
| Annex D | (informative) Apparatus for impact test |