

# DIN EN 12259-9:2019-08 (E)

## Fixed firefighting systems - Components for sprinkler and water spray systems - Part 9: Deluge alarm valves

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	5
4	Product characteristics .....	8
4.1	Operational reliability .....	8
4.1.1	Working pressure .....	8
4.1.2	Range of operation .....	8
4.1.3	Pressure loss due to hydraulic friction loss .....	10
4.1.4	Operational reliability of moving parts .....	10
4.1.5	Avoidance of error in cover plate installation .....	14
4.1.6	Provision of access to sealing assembly for maintenance .....	14
4.1.7	Provision of manual drain connection .....	14
4.1.8	Provision of automatic drain to prevent water columns .....	15
4.2	Durability .....	15
4.2.1	Endurance .....	15
4.2.2	Resistance to ageing of non-metallic components (excluding gaskets, diaphragms and seals) .....	15
4.2.3	Resistance of springs and diaphragms to cyclic operations .....	15
4.2.4	Resistance to deterioration of body, fasteners and covers .....	15
4.2.5	Resistance to deterioration for seating and bearing surfaces .....	16
4.2.6	Resistance to adhesion for sealing assembly and diaphragm elements .....	16
4.3	Additional requirements .....	16
4.3.1	Nominal size .....	16
4.3.2	Connections .....	16
5	Testing, assessment and sampling methods .....	17
6	Assessment and verification of constancy of performance - AVCP .....	17
6.1	General .....	17
6.2	Type testing .....	17
6.2.1	General .....	17
6.2.2	Test samples, testing and compliance criteria .....	18
6.2.3	Test reports .....	20
6.2.4	Shared other party results .....	20
6.3	Factory production control (FPC) .....	20
6.3.1	General .....	20
6.3.2	Requirements .....	21
6.3.3	Product specific requirements .....	23
6.3.4	Initial inspection of factory and of FPC .....	23
6.3.5	Continuing surveillance of FPC .....	24
6.3.6	Procedure for modifications .....	24
6.3.7	Pre-production products (e.g. prototypes) .....	24
7	Marking, labelling and packaging .....	25
7.1	General .....	25
7.2	Deluge alarm valve .....	26

<b>8</b>	<b>Instructions for installation and operation .....</b>	<b>26</b>
	<b>Annex A (normative) Fire exposure test for body and cover .....</b>	<b>27</b>
	<b>Annex B (normative) Strength test for body and cover .....</b>	<b>29</b>
	<b>Annex C (normative) Flow tests for deluge alarm valves .....</b>	<b>30</b>
<b>C.1</b>	<b>Automatic drain valve operation .....</b>	<b>30</b>
<b>C.2</b>	<b>Flow through open drain .....</b>	<b>30</b>
<b>C.3</b>	<b>Hydraulic friction loss test .....</b>	<b>30</b>
	<b>Annex D (normative) Sealing assembly tests .....</b>	<b>32</b>
<b>D.1</b>	<b>Fatigue test for springs and diaphragms .....</b>	<b>32</b>
<b>D.2</b>	<b>Anti-reseating test .....</b>	<b>32</b>
<b>D.3</b>	<b>Differential pressure ratio test .....</b>	<b>32</b>
	<b>Annex E (normative) Performance tests .....</b>	<b>34</b>
<b>E.1</b>	<b>Resistance of body and sealing assembly to leakage and deformation .....</b>	<b>34</b>
<b>E.2</b>	<b>Operational characteristics of a deluge alarm valve .....</b>	<b>34</b>
	<b>Annex F (normative) Resistance to ageing test for non-metallic components (excluding diaphragms, gaskets and seals) .....</b>	<b>36</b>
<b>F.1</b>	<b>Air oven ageing for components normally exposed to air when in the ready condition .....</b>	<b>36</b>
<b>F.2</b>	<b>Warm water ageing for components normally exposed to water when in the ready condition .....</b>	<b>36</b>
	<b>Annex G (normative) Leakage resistance test .....</b>	<b>37</b>
	<b>Annex H (normative) Test for sealing assembly elements - Resistance to adhesion .....</b>	<b>38</b>
	<b>Annex I (normative) Endurance test - Procedure .....</b>	<b>39</b>
	<b>Annex J (normative) Salt mist corrosion test .....</b>	<b>40</b>
<b>J.1</b>	<b>Reagents .....</b>	<b>40</b>
<b>J.2</b>	<b>Apparatus .....</b>	<b>40</b>
<b>J.3</b>	<b>Procedure .....</b>	<b>40</b>
	<b>Annex K (informative) Typical testing schedule and example of test specimen number of deluge alarm valves .....</b>	<b>41</b>
	<b>Bibliography .....</b>	<b>42</b>