ISO 6182-17:2020 (E)

Fire protection — Automatic sprinkler systems — Part 17: Requirements and test methods for pressure reducing valves

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Requirements

- 4.1 Nominal sizes and tolerances
- 4.2 Connections
- 4.3 Rated working pressure
- 4.4 Body and cover
- 4.5 Strength (see 6.4)
- 4.6 Access for maintenance
- 4.7 Components
- 4.8 Leakage and deformation (6.3)
- 4.9 Non-metallic components (excluding gaskets, diaphragms, seals and other elastomeric parts) (see 6.5 and 6.6)
- 4.10 Sealing assembly elements (see 6.7)
- 4.11 Clearances
- 4.12 Operation (see 6.8)
- 4.13 Static leakage (see 6.9)
- 4.14 Durability (see 6.10)

5 Production testing and quality control

6 Tests

- 6.1 Samples
- 6.2 Spring and diaphragm
- 6.2.1 Spring
- 6.2.1.1 General
- 6.2.1.2 Sealing assembly
- 6.2.1.3 Internal bypass
- 6.2.2 Diaphragm
- 6.3 Leakage and deformation (see 4.8)
- 6.3.1 Body leakage (see 4.8.1)
- 6.3.2 Sealing assembly (see 4.8.2)
- 6.3.3 Stem seal and repacking leakage (see 4.8.3)
- 6.4 Strength (see 4.5)
- 6.4.1 Body (see 4.5.1)
- 6.4.2 Diaphragms (see 4.5.2)
- 6.5 Warm-water ageing test for non-metallic components (excluding gaskets, seals and other elastomeric components) (see 4.9)
- 6.6 Air ageing test for non-metallic components (excluding gaskets, seals and other elastomeric components) (see 4.9)
- 6.7 Sealing element tests (see 4.10)
- 6.8 Operation (see 4.12)
- 6.9 Static leakage (90 days) (see 4.13)
- 6.10 Durability (see 4.14)

7 Marking

8 Manufacturer’s installation instructions

Annex A (normative) Tolerances

Page count: 13