

ISO 12239:2021-11 (E)

Smoke alarms using scattered light, transmitted light or ionization

Contents	Page
Foreword	vii
Introduction	viii
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 General requirements	5
4.1 Conformity.....	5
4.2 Optional and additional functions.....	5
4.3 Smoke alarm type.....	5
4.4 Response threshold value of detectors using scattered or transmitted light.....	6
4.5 Alarm condition.....	6
4.5.1 Aural indicator.....	6
4.5.2 Visual indicators.....	6
4.6 External main power source-on visual indicator.....	7
4.7 Fault condition visual indicator — Optional function.....	7
4.8 Visual indicator visibility.....	7
4.9 Smoke alarm signals.....	7
4.10 Test facility.....	7
4.11 Means of calibration.....	7
4.12 User-replaceable components.....	7
4.13 Main power source.....	8
4.13.1 General.....	8
4.13.2 Internal.....	8
4.13.3 External.....	8
4.14 Standby power source.....	8
4.14.1 General.....	8
4.14.2 Monitoring of standby power source.....	9
4.14.3 Standby power source low condition silence — Optional function.....	9
4.15 External power supply equipment.....	9
4.16 Battery connections.....	9
4.17 User-replaceable battery.....	9
4.17.1 General.....	9
4.17.2 Indication.....	9
4.18 Electrical safety.....	10
4.19 Battery — disconnect facility.....	10
4.20 Connection of external connectable devices.....	10
4.21 Terminals for external conductors.....	10
4.22 Protection against the ingress of foreign bodies.....	11
4.23 Interconnectable smoke alarms — Optional function.....	11
4.23.1 General.....	11
4.24 Alarm-silence facility — Optional function.....	11
4.25 Temporary disablement — Optional function.....	12
4.26 Radioactive material in type B smoke alarms.....	12
4.27 Smoke alarms with voice — Optional function.....	12
4.27.1 General.....	12
4.27.2 Voice messages.....	13
4.28 Smoke alarms using radio frequency links — Optional function.....	13

4.28.1	General	13
4.28.2	Response time	13
4.28.3	Radio frequency link range	13
4.28.4	Identification code verification	13
4.28.5	Environmental requirements for radio frequency interconnected smoke alarms	13
4.29	Response to slowly developing fires (drift compensation) — Optional function	14
4.30	Marking	14
4.30.1	General	14
4.30.2	Smoke alarm	14
4.31	Packaging	15
4.32	Hardware documentation	16
4.33	Additional requirements for software-controlled smoke alarms	17
4.33.1	General	17
4.33.2	Software documentation	17
4.33.3	Software design	17
4.33.4	Storage of programs and data	18
5	Tests	18
5.1	General	18
5.1.1	Optional functions	18
5.1.2	Atmospheric conditions for tests	18
5.1.3	Operating conditions for tests	18
5.1.4	Mounting arrangements	19
5.1.5	Tolerances	19
5.1.6	Measurement of response threshold value	19
5.1.7	Provision for tests	19
5.1.8	Test schedule	20
5.1.9	Test report	20
5.2	Directional dependence	21
5.2.1	Object of test	21
5.2.2	Test procedure	21
5.2.3	Requirements	21
5.3	Initial sensitivity	21
5.3.1	Object of test	21
5.3.2	Test procedure	22
5.3.3	Requirement	22
5.4	Repeatability	22
5.4.1	Object of test	22
5.4.2	Test procedure	22
5.4.3	Requirements	22
5.5	Air movement	22
5.5.1	Object of test	22
5.5.2	Test procedure	22
5.5.3	Requirements	23
5.6	Dazzling	23
5.6.1	Object of test	23
5.6.2	Test procedure	23
5.6.3	Requirements	23
5.7	Dry heat (operational)	24
5.7.1	Object of test	24
5.7.2	Test procedure	24
5.7.3	Requirements	24
5.8	Cold (operational)	24
5.8.1	Object of test	24
5.8.2	Test procedure	25
5.8.3	Requirement	25
5.9	Damp heat (operational)	25
5.9.1	Object of test	25
5.9.2	Test procedure	25
5.9.3	Requirements	26
5.10	Sulfur dioxide (SO ₂) corrosion	26
5.10.1	Object of test	26
5.10.2	Test procedure	26
5.10.3	Requirements	27

5.11	Impact (operational)	27
	5.11.1 Object of test	27
	5.11.2 Test procedure	27
	5.11.3 Requirements	28
5.12	Vibration, sinusoidal (operational)	28
	5.12.1 Object of test	28
	5.12.2 Test procedure	28
	5.12.3 Requirements	29
5.13	Vibration, sinusoidal (endurance)	29
	5.13.1 Object of test	29
	5.13.2 Test procedure	29
	5.13.3 Requirements	30
5.14	Extended temperature (operational) — optional function	30
	5.14.1 Object of test	30
	5.14.2 Test procedure	30
	5.14.3 Requirement	31
5.15	Electromagnetic compatibility (EMC) immunity tests (operational)	31
5.16	Fire sensitivity	31
	5.16.1 Object of test	31
	5.16.2 Test procedure	31
	5.16.3 Requirements	33
5.17	Battery-low condition	33
	5.17.1 Object of test	33
	5.17.2 Test procedure	33
	5.17.3 Requirements	34
5.18	85 dBA Sound output — Optional function	34
	5.18.1 Object of test	34
	5.18.2 Method of test	34
	5.18.3 Requirements	35
5.19	70 dBA Sound output — Optional function	35
	5.19.1 Object of test	35
	5.19.2 Method of test	35
	5.19.3 Requirements	36
5.20	Sounder durability	36
	5.20.1 Object of test	36
	5.20.2 Test procedure	36
	5.20.3 Requirements	36
5.21	Interconnectable smoke alarms	37
	5.21.1 Object of test	37
	5.21.2 Test procedure	37
	5.21.3 Requirements	37
5.22	Smoke alarms using radio frequency links	37
	5.22.1 General	37
	5.22.2 Radio frequency range	38
	5.22.3 Failure of radio link tests	39
	5.22.4 Identification codes verification	39
	5.22.5 Environmental tests for radio frequency-interconnected smoke alarms	39
5.23	Alarm-silence facility	40
	5.23.1 Object of test	40
	5.23.2 Test requirement	40
	5.23.3 Requirements	40
5.24	Temporary disablement facility	40
	5.24.1 Object of test	40
	5.24.2 Test procedure	40
	5.24.3 Requirements	41
5.25	Variation in supply voltage	41
	5.25.1 Object of test	41
	5.25.2 Test procedure	41

5.25.3	Requirements	41
5.26	Polarity reversal	42
5.26.1	Object of test	42
5.26.2	Test procedure	42
5.26.3	Requirements	42
5.27	Standby power source	42
5.27.1	Object of test	42
5.27.2	Test procedure	42
5.27.3	Requirements	43
5.28	Electrical safety	43
5.28.1	Object of test	43
5.28.2	Test procedure	43
5.28.3	Requirements	44
5.29	Sequence timing for smoke alarms with voice	44
5.29.1	Object of the test	44
5.29.2	Test procedure	44
5.29.3	Measurements during conditioning	44
5.29.4	Requirements	44
6	Test report	44
Annex A	(normative) Smoke tunnel for response-threshold value measurement	46
Annex B	(normative) Test aerosol for response threshold value measurements	47
Annex C	(normative) Smoke-measuring instruments	48
Annex D	(normative) Apparatus for dazzling test	52
Annex E	(normative) Apparatus for impact test	53
Annex F	(normative) Fire test room	55
Annex G	(normative) Smouldering pyrolysis wood fire (TF2)	58
Annex H	(normative) Glowing smouldering cotton fire (TF3)	61
Annex I	(normative) Flaming plastics (polyurethane) fire (TF4)	64
Annex J	(normative) Flaming liquid (<i>n</i>-heptane) fire (TF5)	67
Annex K	(informative) Information concerning the construction of the smoke tunnel	70
Annex L	(informative) Information concerning the construction of the measuring ionization chamber	72
Annex M	(normative) Test configuration by using radio frequency shield test equipment	74
Annex N	(informative) Compensation for alarm sensitivity drift	76
	Bibliography	80