

DIN EN ISO 21805:2023-07 (E)

Guidance and recommendations on design, selection and installation of vents to safeguard the structural integrity of enclosures protected by gaseous fire-extinguishing systems (ISO 21805:2023)

Contents		Page
European foreword	3
Foreword	4
Introduction	5
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Symbols and abbreviated terms	8
5 Use and limitations	9
6 Safety	10
6.1 Structural safety	10
6.2 Personnel safety	10
7 System design — Pressure-relief venting	10
7.1 General	10
7.2 Extinguishant characteristics	11
7.2.1 Positive and negative pressurization	11
7.2.2 Pressure graphs	11
7.3 Enclosure characteristics	12
7.4 Pressure-relief vent paths	12
7.5 Types of pressure-relief vents	13
7.5.1 General	13
7.5.2 Gravity vents	13
7.5.3 Counterweighted flap vent	13
7.5.4 Electrically-operated vents	14
7.5.5 Pneumatically-operated vent	14
7.5.6 Vent accessories	14
7.6 Pressure-relief vent characteristics	15
7.6.1 Vent efficiency	15
7.6.2 Minimum opening pressure	16
7.6.3 Minimum closing pressure	16
7.6.4 Fire rating	16
7.7 Vent location and mounting	16
7.7.1 Vent location	16
7.7.2 Vent mounting	17
7.8 Pressure-relief vent area calculations	18
7.8.1 Use of agent-specific formulae	18
7.8.2 Vent area requirement (non-liquefiable gases)	19
7.8.3 Vent area requirement carbon dioxide	22
7.8.4 Vent area requirements (liquefiable gases)	22
7.8.5 Leakage	28
7.9 Cascade venting calculations	28
7.9.1 Example calculation 3: Cascade venting calculations for IG-541 (peak discharge)	29
7.9.2 Cascade vent arrangements	30
7.9.3 Venting into adjacent enclosures	31

8	System design — Post-discharge venting	33
9	Acceptance	33
10	Service and maintenance	33
	Annex A (informative) Development of agent-specific formulae for liquefiable gases	35
	Annex B (informative) Method for development of agent-specific formulae for liquefiable gases	40
	Bibliographie	42