

# ISO/TR 7240-9:2022-04 (E)

## Fire detection and alarm systems - Part 9: Test fires for fire detectors

---

<b>Contents</b>		<b>Page</b>
Foreword .....		vi
Introduction .....		vii
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions and abbreviated terms .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.2</b>	<b>Abbreviated terms .....</b>	<b>1</b>
<b>4</b>	<b>Characteristics of test fires .....</b>	<b>2</b>
<b>5</b>	<b>Test laboratory .....</b>	<b>3</b>
<b>5.1</b>	<b>General .....</b>	<b>3</b>
<b>5.2</b>	<b>Fire test room (for all detectors except aspirating smoke detectors) .....</b>	<b>3</b>
<b>5.3</b>	<b>Fire test room and ventilation system (for aspirating smoke detectors) .....</b>	<b>4</b>
<b>5.3.1</b>	<b>Fire test room .....</b>	<b>5</b>
<b>5.3.2</b>	<b>Ventilation system .....</b>	<b>6</b>
<b>5.4</b>	<b>Ambient test condition .....</b>	<b>7</b>
<b>5.5</b>	<b>Instruments .....</b>	<b>8</b>
<b>5.5.1</b>	<b>General .....</b>	<b>8</b>
<b>5.5.2</b>	<b>Obscuration meter .....</b>	<b>8</b>
<b>5.5.3</b>	<b>Measuring ionization chamber (MIC) .....</b>	<b>9</b>
<b>5.5.4</b>	<b>CO measuring instrument .....</b>	<b>11</b>
<b>5.5.5</b>	<b>Spark generator .....</b>	<b>12</b>
<b>6</b>	<b>Test method description .....</b>	<b>13</b>
<b>6.1</b>	<b>General .....</b>	<b>13</b>
<b>6.2</b>	<b>Arrangement .....</b>	<b>13</b>
<b>6.3</b>	<b>Measurement parameters .....</b>	<b>13</b>
<b>6.4</b>	<b>End-of-test parameters .....</b>	<b>13</b>
<b>7</b>	<b>Test fires .....</b>	<b>13</b>
<b>7.1</b>	<b>General .....</b>	<b>13</b>
<b>7.2</b>	<b>Test fire TF1 -- Open cellulosic (wood) fire .....</b>	<b>14</b>
<b>7.2.1</b>	<b>General .....</b>	<b>14</b>
<b>7.2.2</b>	<b>Fuel .....</b>	<b>14</b>
<b>7.2.3</b>	<b>Conditioning .....</b>	<b>14</b>
<b>7.2.4</b>	<b>Preparation .....</b>	<b>14</b>
<b>7.2.5</b>	<b>Arrangement .....</b>	<b>14</b>
<b>7.2.6</b>	<b>Ignition starter .....</b>	<b>15</b>
<b>7.2.7</b>	<b>Test validity criteria .....</b>	<b>15</b>
<b>7.2.8</b>	<b>End-of-test conditions .....</b>	<b>16</b>
<b>7.3</b>	<b>Test fire TF2 -- Smouldering (pyrolysis) wood fire .....</b>	<b>16</b>
<b>7.3.1</b>	<b>General .....</b>	<b>16</b>
<b>7.3.2</b>	<b>Fuel .....</b>	<b>16</b>
<b>7.3.3</b>	<b>Hotplate .....</b>	<b>16</b>
<b>7.3.4</b>	<b>Arrangement .....</b>	<b>16</b>
<b>7.3.5</b>	<b>Heating rate .....</b>	<b>16</b>
<b>7.3.6</b>	<b>End-of-test condition .....</b>	<b>16</b>

7.3.7	Test validity criteria .....	17
7.4	Test fire TF2A and TF2B -- Reduced smouldering (pyrolysis) wood fire .....	19
7.4.1	General .....	19
7.4.2	Fuel .....	19
7.4.3	Hotplate .....	19
7.4.4	Arrangement .....	19
7.4.5	Heating rate .....	20
7.4.6	End-of-test condition .....	20
7.4.7	Test validity criteria .....	20
7.5	Test fire TF3 -- Glowing smouldering cotton fire .....	21
7.5.1	General .....	21
7.5.2	Fuel .....	21
7.5.3	Arrangement .....	22
7.5.4	Ignition .....	22
7.5.5	End-of-test condition .....	22
7.5.6	Test validity criteria .....	23
7.6	Test fire TF3A and TF3B -- Reduced glowing smouldering cotton fire .....	24
7.6.1	General .....	24
7.6.2	Fuel .....	24
7.6.3	Arrangement .....	24
7.6.4	Ignition .....	25
7.6.5	End-of-test condition .....	25
7.6.6	Test validity criteria .....	25
7.7	Test fire TF4 -- Flaming plastics (polyurethane) fire .....	26
7.7.1	General .....	26
7.7.2	Fuel .....	26
7.7.3	Conditioning .....	26
7.7.4	Arrangement .....	26
7.7.5	Ignition .....	27
7.7.6	Method of ignition .....	27
7.7.7	End-of-test condition .....	27
7.7.8	Test validity criteria .....	27
7.8	Test fire TF5 -- Flaming liquid (n-heptane) fire .....	29
7.8.1	General .....	29
7.8.2	Fuel .....	29
7.8.3	Arrangement .....	29
7.8.4	Ignition .....	29
7.8.5	End-of-test condition .....	29
7.8.6	Test validity criteria .....	30
7.9	Test fire TF5A and TF5B -- Reduced flaming liquid (n-heptane) fire .....	32
7.9.1	General .....	32
7.9.2	Fuel .....	32
7.9.3	Arrangement .....	32
7.9.4	Ignition .....	33
7.9.5	End-of-test condition .....	33
7.9.6	Test validity criteria .....	33
7.10	Test fire TF6 -- Liquid (methylated spirit) fire .....	34
7.10.1	General .....	34
7.10.2	TF6 used for detectors with heat sensor .....	34
7.10.3	TF6 used for Point-type flame detectors .....	35
7.11	Test fire TF7 -- Slow smouldering (pyrolysis) wood fire .....	36
7.11.1	General .....	36
7.11.2	Fuel .....	36
7.11.3	Conditioning .....	36
7.11.4	Preparation .....	36
7.11.5	Hotplate .....	36
7.11.6	Arrangement .....	36
7.11.7	Heating rate .....	36
7.11.8	Test validity criteria .....	37
7.11.9	Variables .....	38
7.11.10	End-of-test condition .....	38

7.12	Test fire TF8 -- Low-temperature black-smoke liquid (decalin) fire .....	38
7.12.1	General .....	38
7.12.2	Fuel .....	38
7.12.3	Arrangement .....	38
7.12.4	Volume .....	38
7.12.5	Ignition .....	38
7.12.6	End-of-test condition .....	39
7.12.7	Test validity criteria .....	39
7.13	Test fire TF9 -- Deep-seated smouldering cotton fire .....	40
7.13.1	General .....	40
7.13.2	Fuel .....	40
7.13.3	Arrangement .....	41
7.13.4	Ignition .....	41
7.13.5	End-of-test condition .....	41
7.13.6	Test validity criteria .....	42
<b>Annex A (informative) Information concerning the construction of the measuring ionization chamber .....</b>		<b>43</b>
<b>Annex B (informative) m value for different light beam lengths .....</b>		<b>45</b>
<b>Annex C (informative) y value .....</b>		<b>49</b>
<b>Bibliography .....</b>		<b>53</b>