ISO/TR 7240-9:2022-04 (E)

Fire detection and alarm systems - Part 9: Tes t fires for fire detectors

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Normative references 1

3 Terms, definitions and abbreviated terms 1
3.1 Terms and definitions 1
3.2 Abbreviated terms 1

4 Characteristics of test fires 2

5 Test laboratory 3
5.1 General 3
5.2 Fire test room (for all detectors except aspirating smoke detectors) 3
5.3 Fire test room and ventilation system (for aspirating smoke detectors) 4
5.3.1 Fire test room 5
5.3.2 Ventilation system 6
5.4 Ambient test condition 7
5.5 Instruments 8
5.5.1 General 8
5.5.2 Obscuration meter 8
5.5.3 Measuring ionization chamber (MIC) 9
5.5.4 CO measuring instrument 11
5.5.5 Spark generator 12

6 Test method description 13
6.1 General 13
6.2 Arrangement 13
6.3 Measurement parameters 13
6.4 End-of-test parameters 13

7 Test fires 13
7.1 General 13
7.2 Test fire TF1 -- Open cellulosic (wood) fire 14
7.2.1 General 14
7.2.2 Fuel 14
7.2.3 Conditioning 14
7.2.4 Preparation 14
7.2.5 Arrangement 14
7.2.6 Ignition starter 15
7.2.7 Test validity criteria 15
7.2.8 End-of-test conditions 16
7.3 Test fire TF2 -- Smouldering (pyrolysis) wood fire 16
7.3.1 General 16
7.3.2 Fuel 16
7.3.3 Hotplate 16
7.3.4 Arrangement 16
7.3.5 Heating rate 16
7.3.6 End-of-test condition 16

7.3.7 Test validity criteria 17
7.4 Test fire TF2A and TF2B -- Reduced smouldering (pyrolysis) wood fire 19
7.4.1 General 19
7.4.2 Fuel 19
7.4.3 Hotplate 19
7.4.4 Arrangement 19
7.4.5 Heating rate 20
7.4.6 End-of-test condition 20
7.4.7 Test validity criteria 20
7.5 Test fire TF3 -- Glowing smouldering cotton fire 21
7.5.1 General 21
7.5.2 Fuel 21
7.5.3 Arrangement 22
7.5.4 Ignition 22
7.5.5 End-of-test condition 22
7.5.6 Test validity criteria 23
7.6 Test fire TF3A and TF3B -- Reduced glowing smouldering cotton fire 24
7.6.1 General 24
7.6.2 Fuel 24
7.6.3 Arrangement 24
7.6.4 Ignition 25
7.6.5 End-of-test condition 25
7.6.6 Test validity criteria 25
7.7 Test fire TF4 -- Flaming plastics (polyurethane) fire 26
7.7.1 General 26
7.7.2 Fuel 26
7.7.3 Conditioning 26
7.7.4 Arrangement 26
7.7.5 Ignition 27
7.7.6 Method of ignition 27
7.7.7 End-of-test condition 27
7.7.8 Test validity criteria 27
7.8 Test fire TF5 -- Flaming liquid (n-heptane) fire 29
7.8.1 General 29
7.8.2 Fuel 29
7.8.3 Arrangement 29
7.8.4 Ignition 29
7.8.5 End-of-test condition 29
7.8.6 Test validity criteria 30
7.9 Test fire TF5A and TF5B -- Reduced flaming liquid (n-heptane) fire 32
7.9.1 General 32
7.9.2 Fuel 32
7.9.3 Arrangement 32
7.9.4 Ignition 33
7.9.5 End-of-test condition 33
7.9.6 Test validity criteria 33
7.10 Test fire TF6 -- Liquid (methylated spirit) fire 34
7.10.1 General 34
7.10.2 TF6 used for detectors with heat sensor 34
7.10.3 TF6 used for Point-type flame detectors 35
7.11 Test fire TF7 -- Slow smouldering (pyrolysis) wood fire 36
7.11.1 General 36
7.11.2 Fuel 36
7.11.3 Conditioning 36
7.11.4 Preparation 36
7.11.5 Hotplate 36
7.11.6 Arrangement 36
7.11.7 Heating rate 36
7.11.8 Test validity criteria 37
7.11.9 Variables 38
7.11.10 End-of-test condition 38

7.12 Test fire TF8 -- Low-temperature black-smoke liquid (decalin) fire 38
7.12.1 General 38
7.12.2 Fuel 38
7.12.3 Arrangement 38
7.12.4 Volume 38
7.12.5 Ignition 38
7.12.6 End-of-test condition 39
7.12.7 Test validity criteria 39
7.13 Test fire TF9 -- Deep-seated smouldering cotton fire 40
7.13.1 General 40
7.13.2 Fuel 40
7.13.3 Arrangement 41
7.13.4 Ignition 41
7.13.5 End-of-test condition 41
7.13.6 Test validity criteria 42

Annex A (informative) Information concerning the construction of the measuring ionization chamber 43

Annex B (informative) m value for different light beam lengths 45

Annex C (informative) y value 49

Bibliography 53