ISO 7240-31:2022-09 (E)

Fire detection and alarm systems - Part 31: Resettable line-type heat detectors

Contents

Page

Foreword ... **viii**

Introduction ... **ix**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**

4 Requirements ... **3**

4.1 General ... 3

4.1.1 Conformance ... 3

4.1.2 Heat response classes ... 3

4.2 Individual alarm indication ... 5

4.3 Signalling ... 5

4.4 Repeatability ... 6

4.5 Reproducibility ... 6

4.6 Connection of ancillary devices ... 6

4.7 Manufacturer's adjustments ... 6

4.8 Software ... 6

4.8.1 General ... 6

4.8.2 Software design ... 6

4.8.3 The storage of programs and data ... 6

4.9 Sensing element fault ... 7

4.10 On-site adjustment of response behaviour ... 7

4.11 Maximum ambient temperature test (sensing element) ... 7

4.12 Variation in supply parameters ... 7

4.13 Low voltage fault ... 7

4.14 Fire sensitivity for Class A and ror-only RLTHD ... 7

4.15 Static response temperature test ... 7

4.16 Response times from typical application temperature for ror-only RLTHD ... 8

4.17 Dry heat (operational) sensor control unit ... 8

4.18 Dry heat (endurance) for sensor control unit and sensing element ... 8

4.19 Cold (operational) for sensing element ... 8

4.20 Cold (operational) for sensor control unit ... 8

4.21 Damp heat, steady-state (endurance) for sensor control unit and sensing element ... 8

4.22 Damp heat, cyclic (operational) for sensing element ... 8

4.23 Damp heat, cyclic (operational) for sensor control unit ... 8

4.24 Damp heat, steady-state (operational) for sensor control unit ... 8

4.25 Damp heat, cyclic (endurance) for sensor control unit and sensing element ... 8

4.26 Shock (operational) for sensor control unit ... 8

4.27 Impact (operational) for sensor control unit ... 9

4.28 Impact (operational) for sensing element ... 9

4.29 Vibration, sinusoidal (operational) for sensor control unit ... 9

4.30 Vibration, sinusoidal (operational) for sensing element ... 9

4.31 Vibration, sinusoidal (endurance) for sensor control unit ... 9

4.32 Vibration, sinusoidal (endurance) for sensing element ... 9

4.33 Sulfur dioxide (SO_2) corrosion (endurance) for sensing element ... 9

4.34 Sulfur dioxide (SO_2) corrosion (endurance) for sensor control unit ... 9

4.35 Electromagnetic immunity ... 9

5 Test methods ... **9**

5.1 General ... 9

5.1.1 Atmospheric conditions for tests ... 9

5.1.2 Operating conditions for tests ... 10

5.1.3 Mounting arrangements ... 10

5.1.4 Tolerances ... 10

5.1.5 Procedure for measurement of response time 10
5.1.6 Provision for tests 11
5.1.7 Test schedule 12
5.2 Individual alarm indication 14
5.3 Signalling 14
5.4 Repeatability 14
5.4.1 Object of the test 14
5.4.2 Test procedure 14
5.4.3 Requirements 15
5.5 Reproducibility 15
5.5.1 Object of the test 15
5.5.2 Test procedure 15
5.5.3 Requirements 15
5.6 Connection of ancillary devices 15
5.7 Manufacturer's adjustments 15
5.8 Requirements for software-controlled detectors 15
5.9 Sensing element fault 15
5.9.1 Object of the test 15
5.9.2 Sensing element operational continuity 16
5.9.3 Requirements 16
5.10 On-site adjustment of response behaviour 16
5.11 Maximum ambient temperature test (sensing element) 16
5.11.1 Object of the test 16
5.11.2 Mounting of the sensing element 16
5.11.3 Test procedure 16
5.11.4 Requirements 16
5.12 Variation in supply parameters 16
5.12.1 Object of the test 16
5.12.2 Test procedure 17
5.12.3 Requirements 17
5.13 Low voltage fault 17
5.13.1 Object of the test 17
5.13.2 Test procedure 17
5.13.3 Requirements 17
5.14 Fire sensitivity for Class A and ror-only RLTHD 17
5.14.1 Object of the test 17
5.14.2 Principle 17
5.14.3 Fire test room 17
5.14.4 Test fires 18
5.14.5 Mounting of the specimens 18
5.14.6 Initial conditions 18
5.14.7 Recording of the fire parameters and response times 19
5.14.8 Requirements 19
5.15 Static response temperature test 19
5.15.1 Object of the test 19
5.15.2 Test procedure for non-integrating linear and multipoint RLTHD 19
5.15.3 Test procedure for integrating linear RLTHD 21
5.15.4 Requirements 22
5.16 Response times from typical application temperature for ror-only RLTHD 22
5.16.1 Object of the test 22
5.16.2 Test procedure 22
5.16.3 Requirements 22
5.17 Dry heat (operational) test for sensor control unit 22
5.17.1 Object of the test 22
5.17.2 Reference 22
5.17.3 State of the specimen during conditioning 22
5.17.4 Conditioning 23
5.17.5 Measurements during conditioning 23

5.17.6 Final measurements 23
5.17.7 Requirements 23
5.18 Dry heat (endurance) for sensor control unit and sensing element 23
5.18.1 Object of the test 23
5.18.2 Principle 23
5.18.3 Reference 24
5.18.4 State of the specimen during conditioning 24
5.18.5 Conditioning 24
5.18.6 Final measurements 24
5.18.7 Requirements 25
5.19 Cold (operational) for sensing element 25
5.19.1 Object of the test 25
5.19.2 Reference 25
5.19.3 State of the specimen during conditioning 25
5.19.4 Conditioning 25
5.19.5 Measurements during conditioning 25
5.19.6 Final measurements 25
5.19.7 Requirements 26
5.20 Cold (operational) for sensor control unit 26
5.20.1 Object of the test 26
5.20.2 Reference 26
5.20.3 State of the specimen during conditioning 26
5.20.4 Conditioning 26
5.20.5 Measurements during conditioning 26
5.20.6 Final measurements 26
5.20.7 Requirements 27
5.21 Damp heat, steady-state (endurance) for sensor control unit and sensing element 27
5.21.1 Object of the test 27
5.21.2 Reference 27
5.21.3 State of the specimen during conditioning 27
5.21.4 Conditioning 27
5.21.5 Final measurements 27
5.21.6 Requirements 27
5.22 Damp heat, cyclic (operational) for sensing element 28
5.22.1 Object of the test 28
5.22.2 Principle 28
5.22.3 Reference 28
5.22.4 State of the specimen during conditioning 28
5.22.5 Conditioning 28
5.22.6 Measurements during conditioning 29
5.22.7 Final measurements 29
5.22.8 Requirements 29
5.23 Damp heat, cyclic (operational) for sensor control unit 29
5.23.1 Object of the test 29
5.23.2 Principle 29
5.23.3 Reference 29
5.23.4 State of the specimen during conditioning 29
5.23.5 Conditioning 29
5.23.6 Measurements during conditioning 30
5.23.7 Final measurements 30
5.23.8 Requirements 30
5.24 Damp heat, steady-state (operational) for sensor control unit 30
5.24.1 Object of the test 30
5.24.2 Principle 30
5.24.3 Reference 30
5.24.4 State of the specimen during conditioning 31
5.24.5 Conditioning 31
5.24.6 Measurements during conditioning 31

5.24.7 Final measurements 31
5.24.8 Requirements 31
5.25 Damp heat, cyclic (endurance) for sensor control unit and sensing element 31
5.25.1 Object of the test 31
5.25.2 Principle 32
5.25.3 Reference 32
5.25.4 State of the specimen during conditioning 32
5.25.5 Conditioning 32
5.25.6 Final measurements 32
5.25.7 Requirements 32
5.26 Shock (operational) for sensor control unit 33
5.26.1 Object of the test 33
5.26.2 Reference 33
5.26.3 State of the specimen during conditioning 33
5.26.4 Conditioning 33
5.26.5 Measurements during conditioning 33
5.26.6 Final measurements 33
5.26.7 Requirements 33
5.27 Impact (operational) for sensor control unit 34
5.27.1 Object of the test 34
5.27.2 Reference 34
5.27.3 State of the specimen during conditioning 34
5.27.4 Conditioning 34
5.27.5 Measurements during conditioning 34
5.27.6 Final measurements 34
5.27.7 Requirements 34
5.28 Impact (operational) for sensing element 35
5.28.1 Object of the test 35
5.28.2 Test apparatus 35
5.28.3 State of the specimen(s) during conditioning 35
5.28.4 Conditioning 35
5.28.5 Measurements during conditioning 35
5.28.6 Final measurements 35
5.28.7 Requirements 36
5.29 Vibration, sinusoidal (operational) for sensor control unit 36
5.29.1 Object of the test 36
5.29.2 Reference 36
5.29.3 State of the specimen during conditioning 36
5.29.4 Conditioning 36
5.29.5 Measurements during conditioning 36
5.29.6 Final measurements 36
5.29.7 Requirements 37
5.30 Vibration, sinusoidal (operational) for sensing element 37
5.30.1 Object of the test 37
5.30.2 Reference 37
5.30.3 State of the specimen during conditioning 37
5.30.4 Conditioning 37
5.30.5 Measurements during conditioning 37
5.30.6 Final measurements 37
5.30.7 Requirements 38
5.31 Vibration, sinusoidal (endurance) for sensor control unit 38
5.31.1 Object of the test 38
5.31.2 Reference 38
5.31.3 State of the specimen during conditioning 38
5.31.4 Conditioning 38
5.31.5 Final measurements 38
5.31.6 Requirements 38
5.32 Vibration, sinusoidal (endurance) for sensing element 39

5.32.1 Object of the test 39
5.32.2 Reference 39
5.32.3 State of the specimen during conditioning 39
5.32.4 Conditioning 39
5.32.5 Final measurements 39
5.32.6 Requirements 39
5.33 Sulfur dioxide (SO_2) corrosion (endurance) for sensing element 40
5.33.1 Object of the test 40
5.33.2 Reference 40
5.33.3 State of the specimen during conditioning 40
5.33.4 Conditioning 40
5.33.5 Final measurements 40
5.33.6 Requirements 40
5.34 Sulfur dioxide (SO_2) corrosion (endurance) for sensor control unit 41
5.34.1 Object of the test 41
5.34.2 Reference 41
5.34.3 State of the specimen during conditioning 41
5.34.4 Conditioning 41
5.34.5 Final measurements 41
5.34.6 Requirements 41
5.35 Electromagnetic compatibility (EMC), immunity tests (operational) 42
5.35.1 General 42
5.35.2 State of the specimen during conditioning 42
5.35.3 Final measurements 42
5.35.4 Requirements 42

6 Test report 42

7 Marking 43
7.1 General 43
7.2 Marking of sensor control unit 43
7.3 Marking of sensing element 43
7.4 Marking of functional units 43

8 Data 44
8.1 Hardware documentation 44
8.2 Software documentation 44

Annex A (normative) **Arrangement of the sensing element in the fire test room 46**

Annex B (normative) **Flaming liquid test fires (TF6F, TF6 and TF6S) 48**

Annex C (normative) **Test arrangement for the sensing element of linear heat detectors in the heat tunnel 50**

Annex D (informative) **Apparatus for mounting of the sensing element of linear heat detectors in the heat tunnel 51**

Annex E (normative) **Mounting of the sensing element of multipoint RLTHD in the heat tunnel 52**

Annex F (normative) **Heat tunnel for response time and response temperature measurements 54**

Annex G (informative) **Construction of the heat tunnel 55**

Annex H (normative) **Test arrangement for vibration tests for sensing element 57**

Annex I (normative) **Test apparatus for impact test on the sensing element 58**