ISO 21805:2023-02 (E)

Guidance and recommendations on design, selection and installation of vents to safeguard the structural integrity of enclosures protected by gaseous fire-extinguishing systems

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols and abbreviated terms 2

5 Use and limitations 3

6 Safety 4
6.1 Structural safety 4
6.2 Personnel safety 4

7 System design -- Pressure-relief venting 4
7.1 General 4
7.2 Extinguishant characteristics 5
7.2.1 Positive and negative pressurization 5
7.2.2 Pressure graphs 5
7.3 Enclosure characteristics 6
7.4 Pressure-relief vent paths 6
7.5 Types of pressure-relief vents 7
7.5.1 General 7
7.5.2 Gravity vents 7
7.5.3 Counterweighted flap vent 7
7.5.4 Electrically-operated vents 8
7.5.5 Pneumatically-operated vent 8
7.5.6 Vent accessories 8
7.6 Pressure-relief vent characteristics 9
7.6.1 Vent efficiency 9
7.6.2 Minimum opening pressure 10
7.6.3 Minimum closing pressure 10
7.6.4 Fire rating 10
7.7 Vent location and mounting 10
7.7.1 Vent location 10
7.7.2 Vent mounting 11
7.8 Pressure-relief vent area calculations 12
7.8.1 Use of agent-specific formulae 12
7.8.2 Vent area requirement (non-liquefiable gases) 13
7.8.3 Vent area requirement carbon dioxide 16
7.8.4 Vent area requirements (liquefiable gases) 16
7.8.5 Leakage 22
7.9 Cascade venting calculations 22
7.9.1 Example calculation 3: Cascade venting calculations for IG-541 (peak discharge) 23
7.9.2 Cascade vent arrangements 24

7.9.3 Venting into adjacent enclosures 25

8 System design -- Post-discharge venting 27

9 Acceptance 27

10 Service and maintenance 27

Annex A (informative) Development of agent-specific formulae for liquefiable gases 29

Annex B (informative) Method for development of agent-specific formulae for liquefiable gases 34