

DIN EN 17966:2024-12 (E)

Fire protection equipment - Carbon dioxide extinguishing systems for use on premises - Design and installation (ISO 6183:2022, modified)

Contents		Page
European foreword		6
Introduction		7
1	Scope	8
2	Normative references	8
3	Terms and definitions	8
4	Use and limitations	12
4.1	General	12
4.2	Uses for carbon dioxide systems	12
4.3	Limitations for carbon dioxide systems	12
4.4	Temperature limitations	12
5	Safety	13
5.1	Hazard to personnel	13
5.2	Safety precautions	13
5.2.1	Normally occupied and normally unoccupied areas	13
5.2.2	Warning notices for occupiable areas	14
5.2.3	Warning notices for unoccupiable areas	17
5.3	Electrical hazards	18
5.4	Electrical earthing	19
5.5	Electrostatic discharge	19
6	System design	19
6.1	General	19
6.1.1	Introduction	19
6.1.2	Specifications	20
6.1.3	Working documents	20
6.2	Carbon dioxide supply	20
6.2.1	Quality	20
6.2.2	Quantity	20
6.2.3	Container arrangement	21
6.2.4	Storage containers	22
6.3	Distribution	24
6.3.1	General	24
6.3.2	Piping	25
6.3.3	Fittings	25
6.3.4	Pipe and valve support	25
6.3.5	Valves	26
6.3.6	Nozzles	27
6.4	Enclosures (total flooding)	28
6.4.1	Structural strength	28
6.4.2	Loss through openings	28
6.4.3	Ventilation systems	28
6.5	Detection, actuation and control systems	29
6.5.1	General	29
6.5.2	Shut-down of plant and equipment	29
6.5.3	Automatic detection	29

6.5.4	Operating devices	29
6.5.5	Control equipment	30
6.5.6	Audible alarms and visual indicators	31
7	Carbon dioxide flow and concentration calculations	32
7.1	General	32
7.2	System flow calculations	32
7.2.1	General	32
7.2.2	Friction losses	33
7.2.3	Pressure drop	33
7.2.4	Valves and fittings	34
7.2.5	As-installed calculations	34
7.2.6	Specific requirements	34
7.3	Carbon dioxide concentration requirements	34
7.3.1	Flame extinguishment	34
7.3.2	Inerting	34
7.4	Total flooding quantity	35
7.4.1	General	35
7.4.2	Design quantity	35
7.4.3	KB factor	36
7.5	Design of local application systems	38
7.5.1	General	38
7.5.2	Carbon dioxide requirements	39
7.5.3	Rate by area method	39
7.5.4	Rate by volume method	41
7.6	Duration of protection -- total flooding systems	42
7.7	System performance	43
7.7.1	Discharge time	43
7.7.2	Extended discharge	43
8	Commissioning and acceptance	43
8.1	General	43
8.2	Tests	43
8.2.1	General	43
8.2.2	Enclosure check	44
8.2.3	Review of mechanical components	44
8.2.4	Review of enclosure integrity	45
8.2.5	Review of electrical components	45
8.2.6	Preliminary functional tests	46
8.2.7	System functional operational test	46
8.2.8	Remote monitoring operations (if applicable)	47
8.2.9	Control panel primary power source	47
8.2.10	Completion of functional tests	47
8.3	Completion certificate and documentation	47
9	Inspection, maintenance, testing and training	48
9.1	General	48
9.2	Inspection	48
9.2.1	General	48
9.2.2	Container	48
9.2.3	Hose	48
9.2.4	Enclosures	48
9.3	Maintenance	49
9.3.1	General	49
9.3.2	User's programme of inspection	49
9.3.3	Service schedule	49
9.4	Training	49
Annex A (normative)	Working documents	50
A.1	General	50
A.2	Working documents	50

A.3	Specific details	51
A.3.1	Pre-engineered systems	51
A.3.2	Engineered systems	51
A.4	Completion certificate and documentation	51
Annex B (normative) Carbon dioxide system pipe and orifice size determination		56
Annex C (informative) System performance verification		66
Annex D (informative) General information on carbon dioxide		67
D.1	General	67
D.2	Free efflux	68
D.3	Hazards to personnel	70
Annex E (informative) Examples of calculations		72
E.1	Rate by volume method -- Example 1	72
E.1.1	Hazard	72
E.1.2	Actual dimensions	72
E.1.3	Assumed volume	72
E.1.4	Percent perimeter enclosed	73
E.1.5	Discharge rate for 71 % enclosure	73
E.1.6	Discharge rate	73
E.1.7	Carbon dioxide requirement	73
E.2	Rate by volume method -- Example 2	73
E.2.1	Hazard	73
E.2.2	Actual dimensions	73
E.2.3	Assumed volume	73
E.2.4	Percent perimeter enclosed	74
E.2.5	Discharge rate for 0 % enclosure	74
E.2.6	Discharge rate	74
E.2.7	Carbon dioxide requirement	74
E.3	Rate by area method	74
E.3.1	Hazard	74
E.3.2	Surface dimensions	74
E.3.3	Nozzle location	74
E.3.4	Procedure	74
E.3.5	Total flow rate	74
E.3.6	Carbon dioxide requirement	74
E.4	Total flooding system	75
E.4.1	Storeroom	75
E.4.2	Actual dimensions	75
E.4.3	Assumed volume	75
E.4.4	Additional volume for ventilation	75
E.4.5	Deductible volume	75
E.4.6	Total surface area of all sides	75
E.4.7	Total surface area of all openings	76
E.4.8	Area	76
E.4.9	Carbon dioxide design quantity	76
Bibliography		77