DIN EN 17966:2024-12 (E)

Fire protection equipment - Carbon dioxide extinguishing systems for use on premises - Design and installation (ISO 6183:2022, modified)

Contents

Page

European foreword 6

Introduction 7

1 Scope 8

2 Normative references 8

3 Terms and definitions 8

4 Use and limitations 12
4.1 General 12
4.2 Uses for carbon dioxide systems 12
4.3 Limitations for carbon dioxide systems 12
4.4 Temperature limitations 12

5 Safety 13
5.1 Hazard to personnel 13
5.2 Safety precautions 13
5.2.1 Normally occupied and normally unoccupied areas 13
5.2.2 Warning notices for occupiable areas 14
5.2.3 Warning notices for unoccupiable areas 17
5.3 Electrical hazards 18
5.4 Electrical earthing 19
5.5 Electrostatic discharge 19

6 System design 19
6.1 General 19
6.1.1 Introduction 19
6.1.2 Specifications 20
6.1.3 Working documents 20
6.2 Carbon dioxide supply 20
6.2.1 Quality 20
6.2.2 Quantity 20
6.2.3 Container arrangement 21
6.2.4 Storage containers 22
6.3 Distribution 24
6.3.1 General 24
6.3.2 Piping 25
6.3.3 Fittings 25
6.3.4 Pipe and valve support 25
6.3.5 Valves 26
6.3.6 Nozzles 27
6.4 Enclosures (total flooding) 28
6.4.1 Structural strength 28
6.4.2 Loss through openings 28
6.4.3 Ventilation systems 28
6.5 Detection, actuation and control systems 29
6.5.1 General 29
6.5.2 Shut-down of plant and equipment 29
6.5.3 Automatic detection 29

6.5.4 Operating devices 29
6.5.5 Control equipment 30
6.5.6 Audible alarms and visual indicators 31

7 Carbon dioxide flow and concentration calculations 32
7.1 General 32
7.2 System flow calculations 32
7.2.1 General 32
7.2.2 Friction losses 33
7.2.3 Pressure drop 33
7.2.4 Valves and fittings 34
7.2.5 As-installed calculations 34
7.2.6 Specific requirements 34
7.3 Carbon dioxide concentration requirements 34
7.3.1 Flame extinguishment 34
7.3.2 Inerting 34
7.4 Total flooding quantity 35
7.4.1 General 35
7.4.2 Design quantity 35
7.4.3 KB factor 36
7.5 Design of local application systems 38
7.5.1 General 38
7.5.2 Carbon dioxide requirements 39
7.5.3 Rate by area method 39
7.5.4 Rate by volume method 41
7.6 Duration of protection -- total flooding systems 42
7.7 System performance 43
7.7.1 Discharge time 43
7.7.2 Extended discharge 43

8 Commissioning and acceptance 43
8.1 General 43
8.2 Tests 43
8.2.1 General 43
8.2.2 Enclosure check 44
8.2.3 Review of mechanical components 44
8.2.4 Review of enclosure integrity 45
8.2.5 Review of electrical components 45
8.2.6 Preliminary functional tests 46
8.2.7 System functional operational test 46
8.2.8 Remote monitoring operations (if applicable) 47
8.2.9 Control panel primary power source 47
8.2.10 Completion of functional tests 47
8.3 Completion certificate and documentation 47

9 Inspection, maintenance, testing and training 48
9.1 General 48
9.2 Inspection 48
9.2.1 General 48
9.2.2 Container 48
9.2.3 Hose 48
9.2.4 Enclosures 48
9.3 Maintenance 49
9.3.1 General 49
9.3.2 User's programme of inspection 49
9.3.3 Service schedule 49
9.4 Training 49

Annex A (normative) Working documents 50

A.1 General 50
A.2 Working documents 50

A.3 Specific details 51
A.3.1 Pre-engineered systems 51
A.3.2 Engineered systems 51
A.4 Completion certificate and documentation 51

Annex B (normative) Carbon dioxide system pipe and orifice size determination 56

Annex C (informative) System performance verification 66

Annex D (informative) General information on carbon dioxide 67

D.1 General 67
D.2 Free efflux 68
D.3 Hazards to personnel 70

Annex E (informative) Examples of calculations 72

E.1 Rate by volume method -- Example 1 72
E.1.1 Hazard 72
E.1.2 Actual dimensions 72
E.1.3 Assumed volume 72
E.1.4 Percent perimeter enclosed 73
E.1.5 Discharge rate for 71 % enclosure 73
E.1.6 Discharge rate 73
E.1.7 Carbon dioxide requirement 73
E.2 Rate by volume method -- Example 2 73
E.2.1 Hazard 73
E.2.2 Actual dimensions 73
E.2.3 Assumed volume 73
E.2.4 Percent perimeter enclosed 74
E.2.5 Discharge rate for 0 % enclosure 74
E.2.6 Discharge rate 74
E.2.7 Carbon dioxide requirement 74
E.3 Rate by area method 74
E.3.1 Hazard 74
E.3.2 Surface dimensions 74
E.3.3 Nozzle location 74
E.3.4 Procedure 74
E.3.5 Total flow rate 74
E.3.6 Carbon dioxide requirement 74
E.4 Total flooding system 75
E.4.1 Storeroom 75
E.4.2 Actual dimensions 75
E.4.3 Assumed volume 75
E.4.4 Additional volume for ventilation 75
E.4.5 Deductible volume 75
E.4.6 Total surface area of all sides 75
E.4.7 Total surface area of all openings 76
E.4.8 Area 76
E.4.9 Carbon dioxide design quantity 76

Bibliography 77