

DIN EN 12259-15:2025-06 (E)

Fixed firefighting systems - Components for sprinkler and water spray systems - Part 15: Spray pattern sprinklers with a k-factor of at least K160, extended coverage sprinklers of at least K80 and control mode special application sprinklers

| Contents | | Page |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------|-------------|
| European foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Assessment methods and criteria | 6 |
| 4.1 | Tolerances | 6 |
| 4.2 | Connections | 6 |
| 4.3 | Durability of coated sprinklers | 6 |
| 4.4 | High temperature exposure | 6 |
| 4.5 | Conductivity (C-Factor) | 7 |
| 4.6 | Sensitivity (Air oven) | 7 |
| 4.7 | Leak resistance | 9 |
| 4.8 | Release of the sprinkler at minimum operating pressure (for spray pattern, EC and ECS sprinklers) | 9 |
| 4.9 | Nominal operating temperature | 9 |
| 4.10 | Function (only for CMSA) | 10 |
| 4.11 | Size of water passageways | 11 |
| 4.12 | Sprinkler temperature identification | 11 |
| 4.13 | Water distribution | 12 |
| 4.14 | Actual Delivered Density | 22 |
| 4.15 | Extinguishing performance | 27 |
| 4.16 | Discharge coefficient | 28 |
| 4.17 | Sensitivity (Response time index) | 31 |
| 4.18 | Frame strength | 31 |
| 4.19 | Strength of release element - fusible link type | 32 |
| 4.20 | Strength of release element - bulb type | 33 |
| 4.21 | Water hammer | 36 |
| 4.22 | Strength of deflector | 36 |
| 4.23 | Vibration resistance | 36 |
| 4.24 | Impact test | 37 |
| 4.25 | Freezing | 37 |
| 4.26 | High ambient temperature exposure (90-day test) | 38 |
| 4.27 | Thermal shock | 38 |
| 4.28 | Corrosion | 38 |
| 5 | Marking | 38 |
| 6 | Manufacturer's installation instructions | 39 |
| Annex A (normative) Tolerances | | 41 |
| Annex B (normative) Extinguishing performance | | 42 |

| | | |
|------------|-------------------------------------------------------------------|-----------|
| B.1 | General | 42 |
| B.2 | Values for performance under fire | 42 |
| | Annex C (informative) Actual delivered density (ADD) | 78 |
| | Bibliography | 80 |