

ISO 6182-2:2025-07 (E)

Fire protection - Automatic sprinkler systems - Part 2: Requirements and test methods for sprinkler system alarm valves, check valves, water motor alarms, retard devices and accelerators

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Production testing and quality control | 6 |
| 4.1 | Responsibility | 6 |
| 4.2 | Production body strength test | 6 |
| 4.3 | Production operation test | 6 |
| 4.4 | Production leakage test | 6 |
| 5 | Requirements | 6 |
| 5.1 | Overview | 6 |
| 5.2 | Nominal size | 6 |
| 5.3 | Connections | 6 |
| 5.4 | Rated working pressure | 7 |
| 5.5 | Body and cover | 7 |
| 5.6 | Strength (see 6.2) | 7 |
| 5.7 | Access for maintenance | 7 |
| 5.8 | Components (see 6.3, 6.4 and 6.12) | 7 |
| 5.9 | Leakage (see 6.5) | 8 |
| 5.10 | Non-metallic components (excluding gaskets, seals and other elastomeric parts) (see 6.5, 6.6, 6.7 and 6.11) | 9 |
| 5.11 | Sealing assembly elements (see 6.8) | 9 |
| 5.12 | Clearances (see 6.9) | 9 |
| 5.13 | Hydraulic friction loss (see 6.10) | 13 |
| 5.14 | Endurance (see 6.11) | 13 |
| 5.15 | Operational performance (see 6.12) | 13 |
| 5.16 | Equilibrium time (see 6.15) | 14 |
| 5.17 | Drains (see 6.4) | 15 |
| 5.18 | Alarms (see 6.11) | 15 |
| 5.19 | Retard devices (6.16) | 15 |
| 5.19.1 | General | 15 |
| 5.19.2 | Strength | 15 |
| 5.19.3 | Strainer | 15 |
| 5.19.4 | Support | 16 |
| 5.19.5 | Retard chamber drain | 16 |
| 5.19.6 | Components (see 6.6, 6.7, 6.12) | 16 |
| 5.20 | Height limitations for wet pilot lines (see 6.12) | 16 |
| 5.21 | Water motor alarms (see 6.17) | 17 |
| 5.22 | Water motor alarm connections (see 6.17) | 17 |
| 5.23 | Water motor alarm nozzles and strainers | 17 |
| 5.24 | Water motor alarm operation (see 6.17) | 17 |
| 5.25 | Water motor alarm bodies and covers | 17 |
| 5.26 | Water motor alarm audibility (see 6.17) | 18 |

| | | |
|----------|---|-----------|
| 6 | Tests | 19 |
| 6.1 | Samples | 19 |
| 6.2 | Body strength (see 5.6) | 20 |
| 6.3 | Spring and diaphragm test (see 5.8.5) | 20 |
| 6.4 | Anti-reseating test of dry, preaction and deluge valves (see 5.8.6) | 20 |
| 6.5 | Leakage and deformation tests (see 5.9) | 21 |
| 6.5.1 | Body leakage test | 21 |
| 6.5.2 | Sealing assembly test | 21 |
| 6.5.3 | Wet and check valve leakage | 21 |
| 6.6 | Warm water ageing test for non-metallic components (excluding gaskets and seals and other elastomeric parts) (see 5.10, 5.19 and 5.21) | 21 |
| 6.7 | Air ageing test for non-metallic components (excluding gaskets and seals and other elastomeric parts) (see 5.9, 5.18 and 5.20) | 22 |
| 6.8 | Sealing element tests for valves (see 5.11) | 22 |
| 6.9 | Salt mist corrosion test (see 5.12.2 and 5.12.7) | 23 |
| 6.9.1 | Reagents | 23 |
| 6.9.2 | Apparatus | 23 |
| 6.9.3 | Procedure | 23 |
| 6.10 | Hydraulic friction loss test for valves (see 5.13) | 23 |
| 6.11 | Endurance test (see 5.14, 5.18) | 23 |
| 6.12 | Operational tests (see 5.15, 5.20) | 24 |
| 6.12.1 | General | 24 |
| 6.12.2 | Installation | 25 |
| 6.12.3 | Dry and preaction valve differential | 25 |
| 6.12.4 | Preaction valve operation | 25 |
| 6.12.5 | Preaction operational test in the dry mode (sprinkler operation with detection fault) | 27 |
| 6.13 | Wet valve alarm and sensitivity test (see 5.15) | 27 |
| 6.14 | Wet and check valve ratio test (see 5.15.5) | 27 |
| 6.15 | Equilibrium time test (see 5.16) | 27 |
| 6.16 | Retard chamber (see 5.19) | 28 |
| 6.16.1 | Strength | 28 |
| 6.16.2 | Drainage | 28 |
| 6.17 | Water motor alarm tests (see 5.21) | 28 |
| 6.17.1 | Durability | 28 |
| 6.17.2 | Audibility | 28 |
| 6.17.3 | Strength of inlet connection | 28 |
| 6.17.4 | Water resistance | 28 |
| 7 | Marking | 28 |
| 7.1 | Body | 28 |
| 7.2 | Cast markings | 28 |
| 7.3 | Information to be marked | 29 |
| 8 | Manufacturer's installation instructions | 29 |
| 8.1 | Instructions | 29 |
| 8.2 | Care and maintenance | 29 |