

ISO/TS 7240-9:2006-01 (E)

Fire detection and alarm systems - Part 9: Test fires for fire detectors

Contents	Page
Foreword	iv
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Characteristics of test fires	1
4.1 Description	1
4.2 Measurement parameters	2
5 Test laboratory	3
5.1 Dimensions	3
5.2 Ambient test conditions	3
5.3 Instruments	3
6 Test method	3
6.1 Arrangement	3
6.2 Samples	5
6.3 Profile curves	5
6.4 Recording of data	5
6.5 Fire tests response	6
6.6 End-of-test parameters	6
7 Fire sensitivity classification	7
8 Test fires	9
8.1 General	9
8.2 Test fire TF1 -- Open cellulosic (wood) fire	9
8.3 Test fire TF2 -- Rapid smouldering pyrolysis (wood) fire	11
8.4 Test fire TF3 -- Glowing (smouldering) cotton fire	14
8.5 Test fire TF4 -- Open plastics (polyurethane) fire	16
8.6 Test fire TF5 -- Liquid (heptane) fire	18
8.7 Test fire TF6 -- Liquid (methylated spirit) fire	19
8.8 Test fire TF7 -- Slow smouldering (pyrolysis) wood fire	20
8.9 Test fire TF8 -- Low temperature black smoke (decalin) liquid fire	22
8.10 Test fire TF9 -- Deep seated smouldering cotton fire	25
Annex A (normative) m value for different light beam lengths	27
Annex B (normative) y value	31
Annex C (normative) Optical measuring instrument	33
Annex D (normative) Measuring ionization chamber (MIC)	34
Annex E (normative) Spark-generating equipment	40
Bibliography	41