

DIN EN 16510-2-2:2023-02 (E)

Residential solid fuel burning appliances - Part 2-2: Inset appliances including open fires

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Characteristics | 7 |
| 4.1 | Protection of combustible materials | 7 |
| 4.2 | Carbon monoxide emission (CO) | 8 |
| 4.3 | Nitrogen oxides (NO _x) emissions | 9 |
| 4.4 | Emission of organic gaseous compounds (OGC) | 9 |
| 4.5 | Particulate matter (PM) emissions | 10 |
| 4.6 | Safety and accessibility in use | 10 |
| 4.6.1 | General | 10 |
| 4.6.2 | Flue gas outlet temperature at nominal heat output | 10 |
| 4.6.3 | Flue gas outlet temperature at part load heat output | 10 |
| 4.6.4 | Minimum flue draught at nominal heat output | 11 |
| 4.6.5 | Minimum flue draught at part load heat output | 11 |
| 4.6.6 | Flue gas mass flow at nominal heat output | 11 |
| 4.6.7 | Flue gas mass flow at part load heat output | 11 |
| 4.6.8 | Fire safety of installation to the chimney | 11 |
| 4.7 | Energy economy and heat retention | 11 |
| 4.7.1 | Space heat output at nominal heat output | 11 |
| 4.7.2 | Water heat output, if existing at nominal heat output | 12 |
| 4.7.3 | Efficiency at nominal heat output | 12 |
| 4.7.4 | Space heat output at part load heat output | 12 |
| 4.7.5 | Water heat output, if existing at part load heat output | 12 |
| 4.7.6 | Efficiency at part load heat output | 12 |
| 4.7.7 | Seasonal space heating efficiency at appliance's nominal heat output | 13 |
| 4.7.8 | Energy efficiency | 13 |
| 4.7.9 | Electric power consumption at nominal heat output, if existing | 13 |
| 4.7.10 | Electric power consumption at part load heat output, if existing | 14 |
| 4.7.11 | Standby mode power consumption, if existing | 14 |
| 4.8 | Environmental sustainability | 14 |
| 5 | Descriptive features | 15 |
| 5.1 | Data for potential use with room ventilation systems: type of appliance (in relation to its tightness to the room) | 15 |
| 5.2 | Data for the building's statics: appliance's mass | 15 |
| 5.3 | Materials and construction elements | 16 |
| 5.3.1 | General | 16 |
| 5.3.2 | General stresses | 16 |
| 5.3.3 | Integral boiler or heat exchanger | 16 |
| 5.4 | Risk of burning fuel falling out | 16 |
| 5.5 | Temperature rise in the fuel storage | 16 |
| 5.6 | Temperature rise of the operating components | 16 |
| 5.7 | Spillage of flue gases into the room | 17 |
| 5.7.1 | Possible spillage of CO, if relevant for the fuel type | 17 |
| 5.7.2 | Safety test for spillage of combustion gas and discharge of embers | 17 |

| | | |
|---|--|----|
| 5.7.3 | Open operation | 17 |
| 5.8 | Cleanability | 17 |
| 5.8.1 | Heating surfaces | 17 |
| 5.8.2 | Flueways | 17 |
| 5.8.3 | Ashpan | 17 |
| 5.8.4 | Bottomgrate | 17 |
| 5.8.5 | Damper | 18 |
| 5.8.6 | Fan-cut-out-device | 18 |
| 5.9 | Strength and leak tightness of boiler shells | 18 |
| 6 | Assessment and verification of constancy of performance - AVCP | 18 |
| 6.1 | General | 18 |
| 6.2 | Assessment of performance | 18 |
| 6.2.1 | General | 18 |
| 6.2.2 | Test samples, testing and compliance criteria | 19 |
| 6.3 | Verification of constancy of performance | 20 |
| 6.3.1 | Factory production control (FPC) | 20 |
| Annex A (normative) Test methods | | 25 |
| A.1 | Test environment | 25 |
| A.2 | Test assembly | 25 |
| A.3 | Measurement equipment | 25 |
| A.4 | Test procedures | 25 |
| A.5 | Test results | 32 |
| A.6 | Calculation methods | 32 |
| A.7 | Test report | 32 |
| Annex BA (informative) Example for the possibility to extrapolate the steady-state condition from a curve of temperature measurements of at least 8 h | | 35 |
| Annex ZA (informative) Relationship of this European Standard with Regulation (EU) No. 305/2011 | | 37 |
| ZA.1 | Scope and relevant characteristics | 37 |
| ZA.2 | System of Assessment and Verification of Constancy of Performance (AVCP) | 40 |
| ZA.3 | Assignment of AVCP tasks | 40 |
| Bibliography | | 42 |