DIN EN 16282-1:2026-09 (E)

Equipment for commercial kitchens - Components for ventilation in commercial kitchens - Part 1: General requirements including calculation method

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms, definitions, symbols and abbreviated terms 6
3.1 Terms and definitions 7
3.2 Symbols and abbreviated terms 7

4 Objectives of kitchen ventilation 8

5 Classification of kitchens 9

6 Design principles 9
6.1 General requirements 9
6.2 Heat and pollutant loads 11

7 Ergonomic and hygiene requirements 12
7.1 General 12
7.2 Temperature of room air 12
7.3 Humidity of room air 12
7.4 Air velocity in the room 12
7.5 Noise control 13
7.6 Hygiene requirements 13

8 Design principles 14
8.1 General 14
8.2 Preliminary calculations 14
8.2.1 General 14
8.2.2 Hourly air change rate method based on the kitchen size and type of kitchen 14
8.2.3 Method based on the capture velocity 15
8.2.4 Guide values for ancillary rooms 16
8.3 Airflow rate calculation - detailed method 16
8.3.1 Thermally induced airflow rate 16
8.3.2 Capture airflow rates for kitchen extraction hoods 17
8.3.3 Extract airflows in connection with kitchen extraction hoods 19
8.3.4 Extract airflow rates in connection with kitchen air extraction ceilings 20
8.3.5 Extract airflow to avoid condensation 20

9 Exhaust and supply air systems 21
9.1 Exhaust air systems 21
9.2 Supply air systems 21
9.3 System components 21
9.3.1 System cleaning 21
9.3.2 Supply and extract air components 22
9.3.3 Filters 22
9.3.4 Air openings for outside and outgoing air 22

10 Fossil fuelled catering kitchen appliances 22

Annex A (normative) Tables for calculation 23

Annex B (informative) Air circulation within the room 28

Annex C (informative) Calculation example 30

Bibliography 35