

ISO 307:2007-05 (E)

Plastics - Polyamides - Determination of viscosity number

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Principle	3
5	Reagents and materials	3
5.1	Solvents and reagents	3
5.2	Cleaning liquids	4
6	Apparatus	4
7	Preparation of test samples	5
7.1	General	5
7.2	Samples containing less than 98 % (by mass) polyamide	5
8	Calculation of test portion	6
9	Selection of solvent	6
10	Procedure	7
10.1	Cleaning of the viscometer	7
10.2	Preparation of test solution	7
10.3	Measurement of flow times	9
11	Expression of results	10
12	Repeatability and reproducibility	10
13	Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents	11
14	Test report	11
Annex A (informative)	Determination of the concentration of commercial sulfuric acid (95 % to 98 %) and adjustment to 96 % by titration	13
Annex B (informative)	Determination of the concentration of sulfuric acid (95 % to 98 %) and adjustment to 96 % by flow time measurement in a small capillary viscometer	16
Annex C (informative)	Determination of the concentration of commercial formic acid and adjustment to 90 % by titration	18
Annex D (informative)	Determination of the concentration of commercial formic acid and adjustment to 90 % by density measurement	20
Annex E (informative)	Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents	23
Bibliography		33