

# ISO 22621-1:2007-11 (E)

## Plastics piping systems for the supply of gaseous fuels for maximum operating pressures up to and including 2 MPa (20 bar) - Polyamide (PA) - Part 1: General

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>3</b>
<b>3.1</b>	<b>Geometrical characteristics .....</b>	<b>3</b>
<b>3.2</b>	<b>Materials .....</b>	<b>4</b>
<b>3.3</b>	<b>Material characteristics .....</b>	<b>4</b>
<b>3.4</b>	<b>Related to service conditions .....</b>	<b>5</b>
<b>4</b>	<b>Symbols and abbreviated terms .....</b>	<b>5</b>
<b>4.1</b>	<b>Symbols .....</b>	<b>5</b>
<b>4.2</b>	<b>Abbreviations .....</b>	<b>6</b>
<b>5</b>	<b>Material .....</b>	<b>6</b>
<b>5.1</b>	<b>Material of the components .....</b>	<b>6</b>
<b>5.2</b>	<b>Compound .....</b>	<b>6</b>
<b>5.3</b>	<b>Fusion compatibility .....</b>	<b>8</b>
<b>5.4</b>	<b>Classification and designation .....</b>	<b>9</b>
<b>5.5</b>	<b>Maximum operating pressure MOP .....</b>	<b>9</b>
<b>Annex A (normative)</b>	<b>Assessment of degree of pigment or carbon black dispersion in polyamide compounds .....</b>	<b>10</b>
<b>Annex B (normative)</b>	<b>Chemical resistance .....</b>	<b>14</b>
<b>Annex C (normative)</b>	<b>Resistance to rapid crack propagation (RCP) -- Full-scale test (FST) .....</b>	<b>17</b>
<b>Annex D (normative)</b>	<b>Preparation of test assemblies by electrofusion .....</b>	<b>18</b>
<b>Annex E (informative)</b>	<b>Design guidance .....</b>	<b>24</b>
<b>Annex F (normative)</b>	<b>Hoop stress at burst .....</b>	<b>27</b>
<b>Bibliography .....</b>		<b>29</b>