

DIN EN ISO 62:2008-05 (E)

Plastics - Determination of water absorption (ISO 62:2008)

| Contents | | Page |
|------------------------------|--|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Principle | 6 |
| 4 | Apparatus | 6 |
| 5 | Test specimens | 6 |
| 5.1 | General | 6 |
| 5.2 | Square-shaped test specimens for homogeneous plastics | 7 |
| 5.3 | Test specimens of reinforced plastics affected by anisotropic diffusion effects | 7 |
| 5.4 | Tubular test specimens | 7 |
| 5.5 | Rod-shaped test specimens | 8 |
| 5.6 | Specimens cut from finished products, extrusion compounds, sheets or laminates | 8 |
| 6 | Test conditions and procedures | 8 |
| 6.1 | General | 8 |
| 6.2 | General conditions | 8 |
| 6.3 | Method 1: Determination of amount of water absorbed after immersion in water at 23 °C ... | 9 |
| 6.4 | Method 2: Determination of amount of water absorbed after immersion in boiling water | 9 |
| 6.5 | Method 3: Determination of water-soluble matter lost during immersion | 10 |
| 6.6 | Method 4: Determination of amount of water absorbed after exposure to 50 % relative humidity | 10 |
| 7 | Expression of results | 10 |
| 7.1 | Percentage by mass of water absorbed | 10 |
| 7.2 | Determination of the water content at saturation and the water diffusion coefficient using Fick's laws | 11 |
| 8 | Precision | 12 |
| 9 | Test report | 13 |
| Annex A (informative) | Correlation between water absorption by test specimens and Fick's diffusion laws | 14 |
| Annex B (informative) | Precision statement | 16 |
| Bibliography | | 19 |