DIN 8078:2008-09 (E)

Polypropylene (PP) pipes - PP-H, PP-B, PP-R, PP-RCT - General quality requirements and testing

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Material 4
3.1 General 4
3.2 Proof of long-term hydrostatic strength 5

4 Requirements 10
4.1 Delivery condition 10
4.2 Surface condition 10
4.3 Dimensions and tolerances 10
4.4 Long-term hydrostatic strength 10
4.5 Impact strength test behaviour (inspection by attributes) 10
4.6 Changes after heat treatment 10

5 Testing 11
5.1 Surface condition 11
5.2 Dimensions 11
5.3 Out-of-roundness (ovality) 11
5.4 Long-term hydrostatic strength test 12
5.5 Impact strength test (inspection by attributes) 13
5.6 Heat reversion 14
5.7 Inspection documents 14

Annex A (informative) Explanatory notes 15

Bibliography 17

Figures Figure 1 -- Reference characteristic curves of the long-term hydrostatic strength (minimum curves) for PP-H pipes 6

Figure 2 -- Reference characteristic curves of the long-term hydrostatic strength (minimum curves) for PP-B pipes 7

Figure 3 -- Reference characteristic curves of the long-term hydrostatic strength (minimum curves) for PP-R pipes 8

Figure 4 -- Reference characteristic curves of the long-term hydrostatic strength (minimum curves) for PP-RCT pipes 9

Figure 5 -- Test pieces for long-term hydrostatic test 12

Figure 6 -- Bar-shaped test piece for impact strength test 13

Tables Table 1 -- Coefficients for calculating the reference characteristic curves 5

Table 2 -- Test conditions for the long-term hydrostatic test 11

Table 3 -- Impact strength test pieces 14

Table 4 -- Test conditions for heat treatment 14

Table A.1 -- Guideline values for some properties of PP materials 16