

DIN 16834:2009-10 (E)

Pipes of raised-temperature-resistance polyethylene (PE-RT) - PE-RT Type I and PE-RT Type II - Dimensions

Contents	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Safety factors	5
5 Dimensions and designation	5
5.1 General	5
5.2 Outside diameters, wall thicknesses, S/SDR series and masses	6
5.3 Tolerances on mean outside diameter and out-of-roundness	7
5.4 Tolerances on wall thickness	8
6 Allowable working pressures	9
6.1 Allowable working pressures for pipes conveying water	9
6.2 Allowable working pressures for pipes conveying other liquids	9
7 Form supplied	14
8 Marking	14
8.1 General	14
8.2 Minimum marking information	14
Annex A (informative) Explanatory notes	15
Bibliography	16
Figure Figure 1 -- Outside diameter and wall thickness	5
Tables Table 1 -- Outside diameters, wall thicknesses, S/SDR series and masses	6
Table 2 -- Tolerances on mean outside diameter and out-of roundness	7
Table 3 -- Tolerances on wall thickness	8
Table 4 -- Allowable working pressures for PE-RT type I pipes onveying water, with SF = 1,25	10
Table 5 -- Allowable working pressures for PE-RT type I pipes conveying water, with SF = 1,5	11
Table 6 -- Allowable working pressures for PE-RT type II pipes conveying water, with SF = 1,25	12
Table 7 -- Allowable working pressures for PE-RT type II pipes conveying water, with SF = 1,5	13
Table 8 -- Tolerances for pipe lengths	14