

DIN 8061:2009-10 (E)

Unplasticized polyvinyl chloride (PVC-U) pipes - General quality requirements and testing

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Material (moulding material)	5
4.1	General	5
4.2	Demonstrating long-term hydrostatic strength	5
5	Requirements	7
5.1	Form supplied and surface quality	7
5.2	Dimensions, tolerances and out-of-roundness	7
5.3	Strength characteristics determined by long-term hydrostatic strength testing	7
5.4	Impact strength	8
5.4.1	General	8
5.4.2	Impact strength when testing as in 6.4.1	8
5.4.3	Resistance to external blows	8
5.5	Heat reversion	8
5.6	Resistance to dichloromethane	8
6	Testing	8
6.1	Surface quality	8
6.2	Dimensions and out-of-roundness	8
6.3	Strength characteristics determined by long-term hydrostatic strength testing	8
6.4	Impact strength	10
6.4.1	Impact strength testing	10
6.4.2	Resistance to external blows	10
6.5	Heat reversion	12
6.6	Resistance to dichloromethane	12
6.7	Inspection documents	12
Annex A (informative)	Explanatory notes	13
Bibliography		14
Figures	Figure 1 -- Reference lines for long-term hydrostatic strength (time-to-failure curves) for PVC-U pipes	6
	Figure 2 -- Test piece for long-term hydrostatic strength test	9
Tables	Table 1 -- Test conditions for long-term hydrostatic strength testing	7
	Table 2 -- Test conditions for impact test	10
	Table 3 -- Striker	10
	Table 4 -- Masses and fall heights for pipe series SDR 9 to SDR 21 at level M	11

Table 5 -- Masses and fall heights for pipe series SDR 26 to SDR 34,4 at level H	11
Table 6 -- Test conditions for heat reversion test	12
Table A.1 -- PVC-U properties (guideline values)	13