DIN 8061:2009-10 (E)

Unplasticized polyvinyl chloride (PVC-U) pipes - General quality requirements and testing

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Material (moulding material) 5
4.1 General 5
4.2 Demonstrating long-term hydrostatic strength 5

5 Requirements 7
5.1 Form supplied and surface quality 7
5.2 Dimensions, tolerances and out-of-roundness 7
5.3 Strength characteristics determined by long-term hydrostatic strength testing 7
5.4 Impact strength 8
5.4.1 General 8
5.4.2 Impact strength when testing as in 6.4.1 8
5.4.3 Resistance to external blows 8
5.5 Heat reversion 8
5.6 Resistance to dichloromethane 8

6 Testing 8
6.1 Surface quality 8
6.2 Dimensions and out-of-roundness 8
6.3 Strength characteristics determined by long-term hydrostatic strength testing 8
6.4 Impact strength 10
6.4.1 Impact strength testing 10
6.4.2 Resistance to external blows 10
6.5 Heat reversion 12
6.6 Resistance to dichloromethane 12
6.7 Inspection documents 12

Annex A (informative) Explanatory notes 13

Bibliography 14

Figures Figure 1 -- Reference lines for long-term hydrostatic strength (time-to-failure curves) for PVC-U pipes 6

Figure 2 -- Test piece for long-term hydrostatic strength test 9

Tables Table 1 -- Test conditions for long-term hydrostatic strength testing 7

Table 2 -- Test conditions for impact test 10

Table 3 -- Striker 10

Table 4 -- Masses and fall heights for pipe series SDR 9 to SDR 21 at level M 11

Table 5 -- Masses and fall heights for pipe series SDR 26 to SDR 34,4 at level H 11

Table 6 -- Test conditions for heat reversion test 12

Table A.1 -- PVC-U properties (guideline values) 13