

DIN 16833:2009-09 (E)

Pipes of raised-temperature-resistance polyethylene (PE-RT) - PE-RT Type I and PE-RT Type II - General quality requirements, testing

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Material (moulding material)	5
4.1	General	5
4.2	Demonstrating long-term hydrostatic strength	5
5	Requirements	7
5.1	Form supplied	7
5.2	Surface quality	8
5.3	Dimensions and tolerances	8
5.4	Strength characteristics determined by long-term hydrostatic strength testing	8
5.5	Demonstrating thermal stability by means of long-term hydrostatic strength testing	8
5.6	Heat reversion	8
6	Testing	9
6.1	Surface quality	9
6.2	Dimensions	9
6.3	Out-of-roundness	9
6.4	Strength characteristics determined by long-term hydrostatic strength testing	9
6.5	Heat reversion	10
6.6	Inspection documents	10
Annex A (informative)	Explanatory notes	11
Bibliography		13
Figures	Figure 1 -- Reference lines for long-term hydrostatic strength (time-to-failure curves) for pipes of polyethylene of raised temperature resistance PE-RT type I	6
	Figure 2 -- Reference lines for long-term hydrostatic strength (time-to-failure curves) for pipes of polyethylene of raised temperature resistance PE-RT type II	7
	Figure 3 -- Test piece for long-term hydrostatic strength test	9
Tables	Table 1 -- Test conditions for long-term hydrostatic strength testing	8
	Table 2 -- Thermal stability demonstrated by means of long-term hydrostatic strength testing	8
	Table 3 -- Test conditions for heat reversion test	10
	Table A.1 -- PE-RT properties (guideline values)	12