DIN EN 15836-1:2010-11 (E)

Plastics - Plasticized poly(vinyl chloride) (PVC-P) membranes for inground swimming pools - Part 1: Homogenous membranes of nominal thickness equal to or greater than 0,75 mm

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms, definitions, symbols and abbreviations 5
3.1 Terms and definitions 5
3.2 Symbols 5
3.3 Abbreviations 5

4 Sampling and conditioning 6
4.1 Sampling 6
4.2 Conditioning of test pieces 6

5 PVC-P compound 6
5.1 Characteristics of the compound 6
5.2 Heavy metals and other dangerous substances 6
5.3 Environmental aspects 6

6 Visual characteristics 7
6.1 Appearance 7
6.2 Colour (plain coloured membranes) 7
6.3 Abrasion resistance (printed and/or coated membranes) 7

7 Physico-chemical characteristic 8

8 Dimensional characteristics 8

9 Mechanical characteristics 9

10 Characteristics for durability 9

11 Storage conditions 10

12 Installation, refurbishment, exploitation and maintenance 10

13 Designation and marking 11
13.1 Designation 11
13.2 Marking 11

Annex A (normative) Determination of the contents of $CaCO_3$, heavy metals and other elements 12

Annex B (normative) Assessment of chlorine resistance 13

B.1 Principle 13
B.2 Test liquid 13
B.3 Apparatus 13
B.4 Test pieces 13

B.5 Procedure 13
B.6 Test report 14

Annex C (normative) Assessment of the resistance to staining agents 15

C.1 Principle 15
C.2 Staining agents 15
C.3 Apparatus 15
C.4 Test specimens 15
C.5 Procedure 15
C.6 Expression of results 16
C.7 Test report 16

Bibliography 17