DIN EN 15836-2:2010-11 (E)

Plastics - Plasticized poly(vinyl chloride) (PVC-P) membranes for inground swimming pool s - Part 2: Reinforced membranes of nominal thickness equal to or greater than 1,5 mm

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms, definitions, symbols and abbreviations 6
3.1 Terms and definitions 6
3.2 Symbols 6
3.3 Abbreviations 6

4 Sampling and conditioning 6
4.1 Sampling 6
4.2 Conditioning of test pieces 6

5 Membrane composition 7
5.1 Characteristics of the membrane 7
5.2 Heavy metals and other dangerous substances 7
5.3 Environmental aspects 7

6 Visual characteristics 7
6.1 Appearance 7
6.2 Colour (plain coloured membranes) 8
6.3 Abrasion resistance (printed and/or coated reinforced membranes) 8
6.3.1 Test method 8
6.3.2 Requirement 9

7 Physico-chemical characteristic 9

8 Dimensional characteristics 9

9 Mechanical characteristics 10

10 Characteristics for durability 11

11 Storage conditions 11

12 Installation, refurbishment, exploitation and maintenance 12

13 Designation and marking 12
13.1 Designation 12
13.2 Marking 12

Annex A (normative) Determination of the contents of CaCO3, heavy metals and other elements 13

Annex B (normative) Testing of slip resistance 14

B.1 Principle 14
B.2 Testing person 14

B.3 Test rig 14
B.4 Test liquid 14
B.5 Test specimen 14
B.6 Test procedure 14
B.7 Evaluation 15
B.8 Classification 15
B.9 Test report 15

Annex C (normative) Assessment of chlorine resistance 16

C.1 Principle 16
C.2 Test liquid 16
C.3 Apparatus 16
C.4 Test pieces 16
C.5 Procedure 16
C.6 Test report 17

Annex D (normative) Assessment of the resistance to staining agents 18

D.1 Principle 18
D.2 Staining agents 18
D.3 Apparatus 18
D.4 Test specimens 18
D.5 Procedure 18
D.6 Expression of results 19
D.7 Test report 19

Bibliography 20