

# DIN EN 13245-3:2010-11 (E)

## Plastics - Unplasticized poly(vinyl chloride) (PVC-U) profiles for building applications - Part 3: Designation of PVC-UE profiles

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	6
4	Designation of PVC-UE profiles .....	7
5	Codification system for Data block 3 to Data block 5 .....	8
5.1	Modulus of elasticity in flexure (Data block 3) .....	8
5.2	Nominal linear mass (Data block 4) .....	8
5.3	Heat reversion at 75 °C (Data block 4) .....	9
5.4	Impact resistance (Data block 4) .....	9
5.5	Durability (Data block 5) .....	9
5.5.1	General .....	9
5.5.2	Test methods for ageing .....	10
5.5.3	Methods for assessing of ageing .....	11
5.5.4	Codification for properties after ageing .....	12
6	Required characteristics for Type 3 and Type 4 profiles .....	15
6.1	Resistance to cross cut (only for Type 4 profiles) .....	15
6.2	Thermal resistance (only for Type 3 and Type 4 profiles) .....	15
6.3	Water vapour resistance (only for Type 3 and Type 4 profiles, intended to be used for inside building applications) .....	15
6.4	Peel strength (only for Type 3 profiles) .....	15
7	Optional characteristics .....	15
7.1	Resistance to staining .....	15
7.2	Appearance and finishing of the coating (only for Type 3 and 4 profiles) .....	16
7.2.1	General .....	16
7.2.2	Single colour profiles .....	16
7.2.3	Non-uniform colour and texture profiles .....	16
7.2.4	Gloss .....	16
8	Example of the designation of a PVC-UE profile .....	16
9	Use of reprocessible and recyclable material .....	17
Annex A (normative) Determination of the linear mass .....		18
A.1	Apparatus .....	18
A.2	Test specimens .....	18
A.3	Procedure .....	18
A.4	Calculation and expression of results .....	18
Annex B (normative) Falling weight impact resistance of PVC-UE profiles .....		19
B.1	Principle .....	19
B.2	Apparatus .....	19

<b>B.3</b>	<b>Test specimens</b> .....	<b>20</b>
<b>B.4</b>	<b>Conditioning</b> .....	<b>20</b>
<b>B.4.1</b>	<b>Impact resistance at 23 °C</b> .....	<b>20</b>
<b>B.4.2</b>	<b>Impact resistance at low temperature</b> .....	<b>21</b>
<b>B.5</b>	<b>Procedure</b> .....	<b>21</b>
<b>B.6</b>	<b>Expression of results</b> .....	<b>22</b>
<b>Annex C (normative) Determination of peel strength</b> .....		<b>23</b>
<b>C.1</b>	<b>Principle</b> .....	<b>23</b>
<b>C.2</b>	<b>Apparatus</b> .....	<b>23</b>
<b>C.3</b>	<b>Preparation of test pieces</b> .....	<b>23</b>
<b>C.4</b>	<b>Conditioning</b> .....	<b>24</b>
<b>C.5</b>	<b>Procedure</b> .....	<b>24</b>
<b>C.5.1</b>	<b>Constant-speed tensile test</b> .....	<b>24</b>
<b>C.5.2</b>	<b>Constant-load tensile test</b> .....	<b>24</b>
<b>C.6</b>	<b>Test report</b> .....	<b>25</b>
<b>Bibliography</b> .....		<b>26</b>