

DIN EN 1555-2:2010-12 (E)

Plastics piping systems for the supply of gaseous fuels - Polyethylene (PE) - Part 2: Pipes

Contents		Page
Foreword		4
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms and definitions, symbols and abbreviations	8
4	Material	8
4.1	Compound for pipes	8
4.2	Compound for identification stripes	9
4.3	External reprocessable and recyclable material	9
5	General characteristics	9
5.1	Appearance	9
5.2	Colour	9
6	Geometrical characteristics	9
6.1	Measurement of dimensions	9
6.2	Mean outside diameters, out-of-roundness (ovality) and tolerances	9
6.3	Wall thicknesses and related tolerances	10
6.3.1	Minimum wall thicknesses	10
6.3.2	Tolerance on the wall thicknesses	11
6.4	Circumferential reversion of pipes with a dn equal to or greater than 250 mm	12
6.5	Coiled pipe	13
6.6	Lengths	13
7	Mechanical characteristics	13
7.1	Conditioning	13
7.2	Requirements	13
7.3	Retest in case of failure at 80 °C	15
8	Physical characteristics	15
8.1	Conditioning	15
8.2	Requirements	15
9	Performance requirements	16
10	Marking	16
10.1	General	16
10.2	Minimum required marking	17
10.3	Additional marking	17
Annex A (normative) Pipes with co-extruded layers		18
A.1	General	18
A.2	Geometrical characteristics	18
A.3	Mechanical characteristics	18
A.4	Physical characteristics	18

A.5	Marking	18
A.6	Delamination	18
A.7	Integrity of the structure	19
Annex B (normative) Pipes with peelable layer		20
B.1	General	20
B.2	Geometrical characteristics	20
B.3	Mechanical characteristics	20
B.4	Physical characteristics	20
B.5	Coating adhesion	20
B.6	Marking	21
Annex C (normative) Squeeze-off technique		22
C.1	General Squeeze-off technique	22
C.2	Definitions	22
C.3	Test method	22
Bibliography		23