DIN EN 1555-2:2010-12 (E)

Plastics piping systems for the supply of gaseous fuels - Polyethylene (PE) - Part 2: Pipes

Contents

Page

Foreword 4

Introduction 6

1 Scope 7

2 Normative references 7

3 Terms and definitions, symbols and abbreviations 8

4 Material 8
4.1 Compound for pipes 8
4.2 Compound for identification stripes 9
4.3 External reprocessable and recyclable material 9

5 General characteristics 9
5.1 Appearance 9
5.2 Colour 9

6 Geometrical characteristics 9
6.1 Measurement of dimensions 9
6.2 Mean outside diameters, out-of-roundness (ovality) and tolerances 9
6.3 Wall thicknesses and related tolerances 10
6.3.1 Minimum wall thicknesses 10
6.3.2 Tolerance on the wall thicknesses 11
6.4 Circumferential reversion of pipes with a dn equal to or greater than 250 mm 12
6.5 Coiled pipe 13
6.6 Lengths 13

7 Mechanical characteristics 13
7.1 Conditioning 13
7.2 Requirements 13
7.3 Retest in case of failure at 80 °C 15

8 Physical characteristics 15
8.1 Conditioning 15
8.2 Requirements 15

9 Performance requirements 16

10 Marking 16
10.1 General 16
10.2 Minimum required marking 17
10.3 Additional marking 17

Annex A (normative) Pipes with co-extruded layers 18

A.1 General 18
A.2 Geometrical characteristics 18
A.3 Mechanical characteristics 18
A.4 Physical characteristics 18

A.5 Marking 18
A.6 Delamination 18
A.7 Integrity of the structure 19

Annex B (normative) Pipes with peelable layer 20

B.1 General 20
B.2 Geometrical characteristics 20
B.3 Mechanical characteristics 20
B.4 Physical characteristics 20
B.5 Coating adhesion 20
B.6 Marking 21

Annex C (normative) Squeeze-off technique 22

C.1 General Squeeze-off technique 22
C.2 Definitions 22
C.3 Test method 22

Bibliography 23