

ISO 11299-3:2011-09 (E)

Plastics piping systems for renovation of underground gas supply networks - Part 3: Lining with close-fit pipes

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
3.1	General	1
3.2	Techniques	2
3.3	Characteristics	2
3.4	Materials	2
3.5	Product stages	2
3.6	Service conditions	2
3.7	Joints	2
4	Symbols and abbreviated terms	3
4.1	Symbols	3
4.2	Abbreviated terms	3
5	Pipes at the "M" stage	3
5.1	Materials	3
5.2	General characteristics	4
5.3	Material characteristics	4
5.4	Geometric characteristics	4
5.5	Mechanical characteristics	4
5.6	Physical characteristics	5
5.7	Jointing	5
5.8	Marking	5
6	Fittings at the "M" stage	5
7	Ancillary components	5
8	Fitness for purpose of the installed lining system at the "I" stage	5
8.1	Materials	5
8.2	General characteristics	5
8.3	Material characteristics	5
8.4	Geometric characteristics	6
8.5	Mechanical characteristics	6
8.6	Physical characteristics	7
8.7	Additional characteristics	7
8.8	Sampling	8
9	Installation practice	8
9.1	Preparatory work	8
9.2	Storage, handling and transport of pipes and fittings	8
9.3	Equipment	8
9.4	Installation	9
9.5	Process-related inspection and testing	10
Annex A (normative)	Factory-folded heat-reverted polyethylene (PE) pipe -- Determination of memory ability	11
Bibliography		13