ISO 16486-3:2012-06 (E)

Plastics piping systems for the supply of gaseous fuels - Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing - Part 3: Fittings

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms,definitions,symbolsandabbreviatedterms 2

4 Material 3
4.1 PA-U compound 3
4.2 Material for non-unplasticized polyamide parts 3

5 General characteristics 4
5.1 Appearance 4
5.2 Design 4
5.3 Colour 4
5.4 Electricalcharacteristicsforelectrofusionfittings 4
5.5 Appearance of factory-made joints 4
5.6 Fusioncompatibility 4

6 Geometrical characteristics 5
6.1 Measurement of dimensions 5
6.2 Dimensions of electrofusion sockets 5
6.3 Dimensionsofspigotendfittings 7
6.4 Dimensions of tapping tees 8
6.5 Dimensionsoftransitionfittingstoothermaterials 9

7 Mechanical characteristics 9
7.1 General 9
7.2 Conditioning 9
7.3 Requirements 9

8 Physical characteristics 10
8.1 Conditioning 10
8.2 Requirement 11

9 Chemicalresistanceoffittingsincontactwithchemicals 11

10 Performance requirements 11

11 Marking 11
11.1 General 11
11.2 Minimumrequiredmarkingoffittings 11
11.3 Additionalinformationrequiredonfittingorlabel 12
11.4 Fusion system recognition 12

12 Packaging 12

Annex A (informative)Examplesoftypicalterminalconnectionsforelectrofusionfittings 13

Annex B (normative) Short-term pressure test method 15

Annex C (normative)Tensiletestfitting/pipeassemblies 17

Bibliography 18